Order Product and

Global Sales & Service

Distributor Inventory

Technical Assistance

Literature Request

 RoHS Product List Customer Feedback

Test and Measurement

N. American Sales Reps

Get Support

U.S. Authorized

Distributors

White Papers

Catalog

PRODUCTS & INFORMATION

NEWS & EVENTS

SALES & SUPPORT

Honeywell Sensing and Control

Home> Products > Conductive Plastic Potentiometers > 380 > Product Page

380C32500



380 Series Industrial Potentiometer, Conductive Plastic Element, Solder lug Terminals, 2 W Power Rating, 2.5 kOhm Resistance Value

Actual product appearance may vary.

Features

- Robust nickel-plated brass shaft and bushings
- Conductive plastic element
- · Linear taper
- 100,000 cycle rotational life

Potential Applications

- Electric vehicles
- Personal mobility
- Off-road vehicles
- Welding and heating

- · Manual controls (throttle, joystick)

- Telecommunications

Description

The 380 Series is a robust 2 watt potentiometer that offers the advantages of a conductive plastic element and a 100,000 cycle rotational life. Special tapers and element designs available on a special order.

Supporting Documentation

Dimensions

Accessory: Knobs and Dial Plate

Product Specifications	
Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal	Solder lug
Power Rating	2 W
Resistance Value	2.5 kOhm
Resistance Tolerance	± 10 %
Linearity	± 5 %
Bushing Thread	9,53 mm [0.375 in] x 32 NEF-2A
Bushing Length	9,53 mm [0.375 in]
Bushing Type	Standard
Shaft Diameter	6,35 mm [0.25 in]
Shaft Length	22,23 mm [0.875 in]
Shaft Ending	Slotted
Body	27.8 mm [1.094 in] diameter max. except at terminal standoff
Electrical Taper	Linear
Operating Temperature	-55 °C to 120 °C [-67 °F to 248 °F]
Working Voltage (Max.)	500 V
Rotational Life	100000 cycles
Mechanical Rotation	312°
Availability	Global
Series Name	380
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers



→ Login to iCOM → Login as Rep/AD → Login as Guest → Login to Digital University

