

PRODUCTS & INFORMATION

→ Honeywell.com

NEWS & EVENTS

→ Automation & Control Solutions

SALES & SUPPORT

My Links

LOGIN

Honeywell Sensing and Control

Home > Products > Conductive Plastic > 53 > Product Page

53C325K



53 Series Industrial Potentiometer, Conductive Plastic Element, Solder lug Terminals, 2 W Power Rating, 25 kOhm Resistance Value

Keyword Search

Search for product and support information.


→ Login to iCOM

→ Login as Guest

→ Login to Digital

University


→ Login as Rep/AD



Product Search

Part number search:





→ Specification Search

■ Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- RoHS Product List
- Customer Feedback

Features

· Robust nickel-plated brass shaft and bushings

Actual product appearance may vary.

- Conductive plastic element
- Linear taper
- 25,000 cycle rotational life

Potential Applications

- · Manual controls (throttle, joystick)
- Electric vehicles
- Personal mobility
- Off-road vehicles Welding and heating
- Telecommunications

Description

The 53 Series is an economical potentiometer made with a rugged construction. It offers a 2 watt power rating and the benefits of a conductive plastic element. It is available in a special construction that accepts a rotary switch (purchased separately).

Supporting Documentation



Accessory: Knobs and Dial Plate

Product Specifications	
Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal Type	Solder lug
Power Rating	2 W
Resistance Value	25 kOhm
Resistance Tolerance	± 10 %
Linearity	± 5 %
Bushing Thread	9,53 mm [0.375 in] x 32 NEF-2A
Bushing length	9,53 mm [0.375 in]
Bushing Type	Standard
Shaft Diameter	6,35 mm [0.25 in]
Shaft length	22,23 mm [0.875 in]
Shaft Ending	Slotted
Body	27.8 mm [1.094 in] diameter max. except at terminal standoff

Electrical Taper	Linear
Operating Temperature	-55 °C to 120 °C [-67 °F to 248 °F]
Working Voltage (Max.)	500 V
Rotational Life	25000 cycles
Mechanical Rotation	312°
Availability	Global
Series Name	53
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

Terms & Conditions | Privacy Statement | Site Map

