

**Get Support** 

■ Global Sales & Service

Distributor Inventory Technical Assistance

Customer Feedback

N. American Sales Reps

U.S. Authorized

Distributors

White Papers Literature Request

HOME ABOUT US PRODUCTS & INFORMATION

→ Honeywell.com

**NEWS & EVENTS** 

→ Automation & Control Solutions

SALES & SUPPORT

LOGIN

# **Honeywell Sensing and Control**

Home > Products > Conductive Plastic > 53 > Product Page

#### 53C32K



53 Series Industrial Potentiometer, Conductive Plastic Element, Solder lug Terminals, 2 W Power Rating, 2 kOhm


**Resistance Value** 

# My Links

- → Login to iCOM
- → Login as Rep/AD
- → Login as Guest
- → Login to Digital University

#### **Keyword Search**

Search for product and support information.



#### **Product Search**

#### Part number search:



#### **Features**

 Robust nickel-plated brass shaft and bushings

Actual product appearance may vary.

- Conductive plastic element
- Linear taper
- 25,000 cycle rotational life

#### **Potential Applications**

- · Manual controls (throttle, iovstick)
- Electric vehicles
- Personal mobility
- Off-road vehicles
- Welding and heating
- Telecommunications

### Description

The 53 Series is an economical potentiometer made with a rugged construction. It offers a 2 watt power rating and the benefits of a conductive plastic element. It is available in a special construction that accepts a rotary switch (purchased separately).

#### **Supporting Documentation**





Product Specifications	
Potentiometer Type	Industrial
Element Type	Conductive Plastic
Terminal Type	Solder lug
Power Rating	2 W
Resistance Value	2 kOhm
Resistance Tolerance	± 10 %
Linearity	± 5 %
Bushing Thread	9,53 mm [0.375 in] x 32 NEF-2A
Bushing length	9,53 mm [0.375 in]
Bushing Type	Standard
Shaft Diameter	6,35 mm [0.25 in]
Shaft length	22,23 mm [0.875 in]
Shaft Ending	Slotted
Body	27.8 mm [1.094 in] diameter max. except at terminal standoff
Electrical Taper	Linear

Operating Temperature	-55 °C to 120 °C [-67 °F to 248 °F]
Working Voltage (Max.)	500 V
Rotational Life	25000 cycles
Mechanical Rotation	312°
Availability	Global
Series Name	53
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

Terms & Conditions | Privacy Statement | Site Map

## For Reference Only

