



M 4LS1
 DRAWING NUMBER
 ISSUE 13
 REVISIONS
 A CO15200 RER JUN 5
 B CO22566 M B F 20 MAR 67
 C CO23403 D M W 1 OCT 68
 D CO25152 G C H 22 APR 69
 E CO26198 M B S 5 NOV 69
 F CO26824 M B S 6 JAN 70
 G CO50952-G WJM 24 JUN 83
 H CO53005-D C J H 1 AUG 84
 J CO65814-E G R T 26 NOV 90
 PO-50378-003
 DRAWN
 R E R 17 JUN 65
 CHECK
 L D D 22 JUN 65
 CHECK
 W C S 22 JUN 65
 CHECK
 W C S 22 JUN 65
 RELEASE NO.
 REPLACES
 M 4LS1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-BELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS	ELECTRICAL DATA	SCALE 1/2 TO 1
OPERATING FORCE ----- 9 LB MAX	CONTACT ARRANGEMENT (SEE CIRCUIT DIAGRAM)	DO NOT SCALE PRINT
RELEASE FORCE ----- 2 LB MIN	10A-120, 240, OR 480 VAC; 1/3 HP - 120 VAC 3/4 HP - 240 VAC; 0.8A - 115 VDC; 0.4A - 230 VDC .1A - 550 VDC PILOT DUTY: 600 VAC MAX	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ±
DIFFERENTIAL TRAVEL ----- .040 MAX		
OVERTRAVEL ----- .250 MIN		
SWITCH-BASIC REPLACEMENT ----- 2MN11		WEIGHT

NOTE -
 $\triangle 2$ SEAL TO BE FURNISHED BY USER