AML21FBA2AA

Image Not Available

AML21 Series, Electronic Control Pushbutton, Rectangular, Standard Bezel, Lighted, 1 Incandescent Lamp, SPDT, Momentary Action, Snap in panel mount

Features

- 1, 2, or 4 poles.
- Silver or gold contacts.
- Full guard bezel option.
- Momentary or 2-level alternate action (push-on, push-off).
- UL recognized, CSA certified.
- Lamps can be furnished installed or ordered separately.
- Lamp circuit independent of switch circuit.

Notice

Button caps for MICRO SWITCH™ AML Pushbuttons are sold separately. Please see the links at the left for information on the buttons caps and other AML accessories.

Product Specifications	
Product Type	MICRO SWITCH™ Pushbutton
Housing Type	Rectangular
Circuitry	SPDT
Action	Momentary Action
Mounting	Snap-in Panel
Lamp Type	Lighted, 1 Incandescent Lamp
Termination	.110 x .020 (Solder or Quick-Connect)
Ampere/Voltage Range (Resistive Load)	0.4-2 A @ 0.5-30 Vdc,0.4-2 A @ 0.5 -250 Vac,0.4-3 A @ 0.5-125 Vac
LED/Lamp/Neon Voltage	No Lamp Installed
Comment	use AML51 button
Availability	Global
UNSPSC Code	30211913
UNSPSC Commodity	30211913 Push button switches
Series Name	AML21

AML PUSHBUTTON AND INDICATOR SERIES

SOLID STATE SWITCH AML 10 SERIES

.060-.187 PANEL THICKNESS

.020 X .110 AND .025 SQUARE TERMINATION

ELECTRONIC CONTROL SWITCH AML 20 SERIES

.020 X .110 AND .025 SQUARE TERMINATION

NOTE:
⚠ SINGLE POLE VERSION

POLE 1 — POLE 2

SWITCH TERMINATION .020 X .110 AND .020 X .029 ⚠ 2 POLE VERSION   LAMP TERMINATION .025 SQUARE

POLE 1 & 2 — POLE 3 & 4

NO / C / NC / C / NO

POWER SWITCH AML 30 SERIES

.020 X .187 TERMINATION

LINE POWER IND AML 43 SERIES

INDICATORS AML 40 SERIES

.020 X .110 AND .025 SQUARE TERMINATION

NOTE:
1— SINGLE LAMP TERMINATION IDENTIFIED BY "A"

NOTE:
1— SINGLE LAMP TERMINATION IDENTIFIED BY "B". DUAL LAMP TERMINATION IDENTIFIED BY "A" AND "C".

.020 X .110 AND .025 SQUARE TERMINATION

.020 X .110 AND .025 SQUARE TERMINATION

NOTE—
TOP OF HIGH BEZEL HOUSINGS ARE .19 FROM PANEL

L.E.D.

NEON

PANEL CUTOUTS

WITHOUT BARRIERS			SHORT BARRIER		LONG BARRIER
6,35±0,15 X 19,0±0,15 / .250±.005 X .750±.005	19,0±0,15 SQUARE / .750±.005	19,0±0,15 X 29,0±0,15 / .750±.005 X 1.141±.005	19,0±0,15 23,25±0,15 / .750±.005 .915±.005	19,0±0,15 X 33,3±0,15 / .750±.005 X 1.310±.005	23,25±0,15 X 29,0±0,15 / .915±.005 X 1.141±.005

MASTER REDUCED

MICRO SWITCH a Honeywell Division
FED. MFG CODE 91929

AML PUSHBUTTONS & INDICATORS

CATALOG LISTING
AML 10 20 30 40
SERIES CHART 1

SCALE FULL
DO NOT SCALE PRINT
TOLERANCES

THIRD ANGLE PROJECTION

CATALOG LISTING: AML 10 20 30 40 SERIES CHART 1
PAGE 1 OF 1
REPLACES AML 10, 20, 30 & 40 SERIES
RELEASE NO CO-78498
ISSUE M 6

REVISIONS
A C095297 GJW 8 JUL 99
B 201477 GJW 9 OCT 00
C 201566 CSI 20 OCT 00
D 201696 DLT 14 NOV 00
E 202971 CSI 30 APR 01

RASTER
DRAWN JAK 17 JUN 94
CHECK JAF 11 JUL 94