



3X 6-32 UNC X (.219) BINDING HEAD COMBINATION TERMINAL SCREW AND CUPWASHER

**NOTE**  
△ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

**CHARACTERISTICS**

OPERATING FORCE ----- 9-13 OZ  
RELEASE FORCE ----- 4 OZ MIN  
DIFFERENTIAL TRAVEL-- .0004 - .0020  
OVERTRAVEL ----- .219 MIN

**ELECTRICAL DATA**

CONTACT ARRANGEMENT  
S P D T  
15A - 125, 250 OR 480 VAC, 2A - 600 VAC  
1/8HP - 125 VAC; 1/4HP - 250 VAC  
CODE L74 1/2A - 125 VDC; 1/4A - 250 VDC  
-L288-  
-L306-  
-L315-  
16A 250V ~ T85 5E4

**SCALE FULL**

DO NOT SCALE PRINT  
UNLESS OTHERWISE NOTED  
DIMENSIONS ARE IN INCHES  
**TOLERANCES ARE:**  
ONE PLACE (.0) ± .030  
TWO PLACE (.00) ± .015  
THREE PLACE (.000) ± .005  
ANGLES ±

WEIGHT .120 LB

**BZ-2RQ66**  
PAGE 1 OF 1

**M**  
DRAWING NUMBER

8  
ISSUE

REPLACES

RELEASE NO.

CHECK

29 AUG 05

29 AUG 64

2, APR 64

27 MAR 64

27 MAR 64

FORMTEK  
FO-80376

DRAWN