



NOTE -  
 ▲ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON 1.000 ± .002 CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

**CHARACTERISTICS**

OPERATING FORCE ----- 7 OZ MAX  
 RELEASE FORCE ----- 1 1/2 OZ MIN  
 DIFFERENTIAL TRAVEL ----- .008-.040  
 OVERTRAVEL ----- .094 MIN

**ELECTRICAL DATA**

CONTACT ARRANGEMENT  
 SINGLE POLE DOUBLE THROW  
 SPLIT CONTACT

UNDERWRITERS' LAB. INC. LISTED RATING  
 L4- 5 A-250 VAC



**SCALE FULL**

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED  
 DIMENSIONS ARE IN INCHES  
**TOLERANCES ARE:**  
 ONE PLACE (.0) ± .030  
 TWO PLACE (.00) ± .015  
 THREE PLACE (.000) ± .005  
 ANGLES ±

WEIGHT .078 LB

M BZ-3YWT822  
 DRAWING NUMBER  
 ISSUE  
 REVISIONS  
 A C016738 GCH 7 DEC 62  
 B C020799 WEG 5 NOV 65  
 C C034506 RER 18 JUL 75  
 D C069351-D JWB 18 JUL 91  
 E C070184-G GJW 16 MAR 92  
 F C075204-B WLS 1 FEB 94  
 G C075204-B WLS 1 FEB 94  
 H C077590 DLT 10 JUN 94  
 FO-50378  
 GCH 7 DEC 62  
 CHECK  
 DAW  
 DRAWN  
 RELEASE NO.  
 REPLACES