9001SKR8P1RH25

Pushbutton, Illuminated, Momentary (Push/Pull) - Maintained (Neutral)



List Price		
Availability		

Technical Characteristics

Bezel Material	Plastic	
Button/Cap Color	Red	
Ampere Rating	10A	
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211 03 - CE Marked	
Button Type	Snap-In Mushroom (1.63 Inch)	
Guard Type	Full Guard	
Catalog Reference Number	9001CT0001	
Contact Configuration	1 N.C./1 N.C. (Late Opening)	
Contact Material	Silver Alloy	
Enclosure Type	Water tight, Dust tight, Oil tight and Corrosion Resistant (Indoor/Outdoor)	
Enclosure Rating	NEMA 4/4X/13	
Head Type	Round	
Light Module Supply Voltage	110/120VAC@50/60Hz	
Light Module Type	Transformer	
Maximum Voltage Rating	600V	
Mounting Type	Panel	
Mounting Position	All	
Number of Operators	1	
Operator Action	Momentary (Push/Pull) - Maintained (Neutral)	
Operator Type	Illuminated	
Terminal Type	Screw Clamp	
Size	30mm	
Туре	SK	
Utilization Category	AC15 - DC13	

Shipping and Ordering

21429 - Push Buttons, Corrosion Resistant, Type SK & SKY	
CP1	
785901042990	
1	
0.54 lbs.	
Non-Stock Item: This item is not normally stocked in our distribution facility.	
Υ	

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 06/08/2009 16:22:50

