

ILB BT ADIO MUX-PANEL

Order No.: 2884509

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2884509>

Wireless MUX wireless set 2 with PANEL directional antenna

 Bluetooth**Commercial data**

EAN	4046356049696
Pack	1 Pcs.
Customs tariff	85176200
Weight/Piece	1.175 KG
Catalog page information	Page 243 (AX-2007)

Product notesWEEE/RoHS-compliant since:
07/18/2008

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Wireless interface**

Name	Bluetooth
Frequency range	2.402 GHz ... 2.48 GHz (ISM bandwidth)
Transmission capacity	12 dBm (16 mW, controlled automatically)

Antenna

Assembly instructions	PANEL radio link antenna, 8 dBi, with fixing bracket, 1 m cable
No.	1
Type of connection	MCX (male)

Power supply for module electronics

Type of connection	Inline connectors
Supply voltage	24 V DC
Range of supply voltages	19.2 V DC ... 30 V DC (including ripple)
Supply current	< 100 mA

Digital inputs

Input name	Digital inputs
Type of connection	Spring-cage connection
Connection system	1-wire
Number of inputs	16
Filter time	500 µs
Input characteristic curve	IEC 61131-2 type 1

Digital outputs

Output name	Digital outputs
Type of connection	Spring-cage connection
Connection system	1-wire
Number of outputs	16
Maximum output current per channel	500 mA
Protective circuitry	Short circuit protection, overload protection, protected against reverse voltages

Analog inputs

Number of inputs	2
Input name	Analog inputs
Description of the input	Single ended
Voltage input signal	0 V ... 10 V
Current input signal	0 mA ... 20 mA
Measured value resolution	12 bits

Analog outputs

Number of outputs	2
-------------------	---

Output name	Analog outputs
Voltage output signal	0 V ... 10 V
Current output signal	0 mA ... 20 mA
DAC resolution	12 bits
General data	
Width	95 mm
Height	120 mm
Depth	55 mm
Weight	1300 g
Ambient temperature (operation)	-25 °C ... 60 °C
Permissible humidity (operation)	75 % (On average, no condensation)
Air pressure (operation)	795 hPa ... 1080 hPa (up to 2000 m above mean sea level)
Degree of protection	IP20
Class of protection	III, VDE 0106
Mechanical tests	Shock according to IEC 60068-2-29 25g
	Vibration (operation) in acc. with IEC 60068-2-6:1982 5g
Diagnostics messages	Short circuit / overload of the digital outputs LED
	Wireless connection FS LED
	Logic and actuator voltage LED
	Link quality of the wireless connection 4 LEDs
Mounting type	DIN rail

Funkzulassungen	Australien (Sonderregelung: Bitte Rücksprache nehmen mit Sebastian Hube, shube@phoenixcontact.com)
	Belgien
	Bulgarien
	Dänemark
	Germany
	Estland
	Finnland
	France
	Griechenland
	Great Britain
	Irland
	Island
	Israel
	Italy
	Kanada
	Lettland
	Lichtenstein
	Litauen
	Luxemburg
	Malta
	Niederlande
	Norwegen
	Österreich
	Polen
	Portugal
	Rumänien
	Russland (Spezielle Vereinbarung für den Import zwischen Kunden und Phoenix Contact benötigt. Nähere Information bei Sebastian Hube, shube@phoenixcontact.com)
	Schweden
	Schweiz
	Singapur
	Slowakei
	Slowenien
	Spanien
	Südafrika
	Tschechien
	Türkei
PHOENIX CONTACT GmbH & Co. KG http://www.phoenixcontact.de	Ungarn
	USA
	Cyprus (rep.)

Certificates / Approvals



Certification CUL, UL

Accessories

Item	Designation	Description
Antennas		
2867610	RAD-ISM-2400-ANT-PAN-8-0	Panel antenna, degree of protection IP55, 8 dBi gain, linear vertical, SMA (female), impedance 50 ohms, apex angle h/v 75°/70°
General		
3022276	CLIPFIX 35-5	Snap-on end bracket, for NS 35/7.5 or NS 35/15 DIN rail, can be fitted with Zack strip ZB 5 and ZBF 5, terminal strip marker KLM 2 and KLM, parking facility for FBS...5, FBS...6, KSS 5, KSS 6, width: 5,15 mm, color: gray
Software		
2692377	FL WST BASIC DEMO CD	Simulation software for supporting the planning of wireless systems in industrial environments. Their functionality is limited with regard to the memory options as compared with the full version FL WST BASIC.

Address

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2009 Phoenix Contact
Technical modifications reserved;