



LLE101101



LLE Series Liquid Level Sensor with Polysulphone housing; Enhanced; Type 1; -40°C to 125°C; 250 mm lead wires; Vamac seal washer

Actual product appearance may vary.

Features

- Solid state reliability - no moving parts
- Miniature size
- Microprocessor compatible
- Very large choice of sensing media
- Fast response
- Cost effective
- Polysulphone sensor housing suitable for hygiene applications
- Options available for internal or external mounting

Potential Applications

- Automotive on board
- Home appliances
- Food and beverage processing
- Compressors
- Machine tools
- Vending machines

Description

The LLE series of enhanced liquid level sensor uses a photo-transistor trigger which provides a digital output that denotes the presence or absence of liquid. This series incorporates reverse polarity, over voltage, short circuit and transient protection.

Product Specifications	
Sensor Type	Enhanced Sensor
Operating Temperature Range	-40 °C to 125 °C [-40 °F to 257 °F]
Storage Temperature Range	-40 °C to 125 °C [-40 °F to 257 °F]
Housing Material	Polysulphone
Housing Type	Type 1
Supply Voltage	5.0 Vdc to 12.0 Vdc
Output Type	High in air
Application Type	Variable
Termination Type	250 mm lead wires
Seal Washer	Vamac rubber

Stainless-Steel Nut	Yes
Dome Dimension	3,5 mm radius
Thread Dimension	M12 x 1 x 8g
Hex Dimension	19 mm [0.75 in]
Pressure Range	0 to 5 bar
Supply Current	5 mA nom.
Output Sink Current	40 mA max. @ 25 °C
Repeatability	1 mm [0.04 in]
Hysteresis (dependant on liquid)	2 mm [0.08 in]
Response Time - Rising Liquid	50 µs
Response Time - Falling Liquid	1 s max. (in ethanol)
Availability	Global
Accessories	41001458001W
Comment	Enhanced device incorporating circuit protection.
UNSPSC Code	411121
UNSPSC Commodity	411121 Transducers
Series Name	LLE