

HBL4715C -- Twist-Lock Flanged Receptacle



2P3W, 15A 125V, L5-15R, White Nylon


Product Specifications

Product Type



Product Item	Flanged Receptacle
Wiring Scheme	2 Pole, 3 Wire Grounding
Amperage	15A
Voltage	125V AC
NEMA Configuration	L5-15R
Item Style	Standard
Device Color	White
Horsepower	0.5
Terminal Retainer Material	Clear polycarbonate
Terminal Clamp Material	.062" cold rolled steel-nickel-plated
Terminal Screw Material	#8-32 Brass (white finish on neutral screw when used)
Ground Screw Material	Brass (green finish)

Body Contact Carrier Material	Natural White Nylon
Contact Spring Material	Brass
Spring Binding Plate Material	Brass
Flanged Casing Material	Natural White Nylon
Mounting Screw Material	Nickel-plated Brass Round head screws
Ground Contact Material	.032" Bronze
Ratings	Molded into face.
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30 C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	15A #14AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Listings	UL/CSA
Catalog Page	Click here for catalog page B12
Brochures	Click here for product brochure
Hubbellnet	Click here for Hubbellnet
Catalog Section	Click here for Section-B
UPC Number	78358517100
Weight in LBs	0.15



TWIST-LOCK® Devices


2 Pole, 3 Wire Grounding

15 Ampere, 125, 250 Volts and 277 Volts AC

Angle Devices, Flanged Inlets, and Flanged Receptacles




HBL4720CA




HBL4715C



HBL4715



HBL4716C



HBL4716



IP20 SUITABILITY Angle Plugs

Description	Cord Dia.	Catalog Numbers		
Insulgrip® plug, 8 position angle, black and white nylon. Multiple drive screws.	.325"-.655" (8.3-16.6)	HBL4720CA	HBL4570CA	HBL4770CA



NEMA L5-15P
15A 125V
UL/CSA
0.5 HP



NEMA L6-15P
15A 250V
UL/CSA
1.5 HP



NEMA L7-15P
15A 277V AC
UL/CSA
2 HP

IP20 SUITABILITY Angle Connector Body

Description	Cord Dia.	Catalog Number		
Insulgrip connector body, 8 position angle, black and white nylon. Multiple drive screws.	.325"-.655" (8.3-16.6)	HBL4729CA	-	-



NEMA L5-15R
15A 125V
UL/CSA



NEMA L6-15R
15A 250V
UL/CSA



NEMA L7-15R
15A 277V AC
UL/CSA

Flanged Receptacles

Description	Catalog Numbers		
Insulgrip flanged receptacle, nylon casing, back wired.	HBL4715C	HBL4585C	HBL4785C
Stainless steel casing, brown phenolic.	HBL4715	HBL4585	HBL4785
Corrosion resistant, stainless steel casing, yellow melamine.	HBL47CM15	-	-



NEMA L5-15R
15A 125V
UL/CSA



NEMA L6-15R
15A 250V
UL/CSA



NEMA L7-15R
15A 277V AC
UL/CSA

Flanged Inlets

Description	Catalog Numbers		
Insulgrip flanged inlet, nylon casing, back wired.	HBL4716C	HBL4586C	HBL4786C
Stainless steel casing, brown phenolic.	HBL4716*	HBL4586*	HBL4786*
Corrosion resistant, stainless steel casing, yellow melamine.	HBL47CM16*	-	-



NEMA L5-15P
15A 125V
UL/CSA



NEMA L6-15P
15A 250V
UL/CSA



NEMA L7-15P
15A 277V AC
UL/CSA

Notes: See pages B-66 and B-67 for accessories.

Only plugs are HP rated.

HP ratings are AC only.

*These flanged inlets will not accept Valise® connector bodies.