



## HBL5364VY -- Valise Plug



2P3W, 20A 125V, 5-20P, Yellow Nylon.

## Product Specifications

<b>Product Type</b>	 <p><b>Plugs</b></p>
<b>Body Style</b>	Straight
<b>Standard</b>	NEMA
<b>Amperage</b>	20A
<b>Voltage</b>	125V
<b>Poles and Wires</b>	2 Pole, 3 Wire Grounding
<b>Hospital Grade ?</b>	No
<b>Plug/Connector Grade</b>	Valise
<b>Color</b>	 <p><b>Yellow</b></p>
<b>NEMA No.</b>	5-20P
<b>Horsepower</b>	1
<b>Cord Dia.</b>	.220"-.660" (5.6-16.8)

<b>Description</b>	Straight Blade Plug
<b>Type</b>	2 Pole, 3 Wire, Grounding
<b>Rating</b>	20A,125V
<b>Certification</b>	UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280
<b>IP Suitability</b>	IP20
<b>Housing Material</b>	Nylon - Yellow
<b>Cord Clamp Material</b>	Noryl (Polyphenylene Oxide)
<b>Contact Blades Material</b>	.060" (1.5) Brass
<b>Ground Contact Blade Material</b>	.040" (1.0) Copper Alloy
<b>Terminal Screw Material</b>	Steel (copper or nickel finish)
<b>Ground Screw Material</b>	Steel (green finish)
<b>Wire Clamps Material</b>	.062" (1.8) Steel-nickel finish
<b>Dielectric Voltage</b>	Withstands 2,000V minimum.
<b>Current Interrupting</b>	Certified for current interrupting at full rated current.
<b>Temperature Rise</b>	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
<b>Terminal Identification</b>	Terminals identified in accordance with UL498 (Brass, White, Green).
<b>Terminal Accommodation</b>	#18-#10 AWG copper stranded conductor
<b>Product Identification</b>	Permanent part of device
<b>Flammability</b>	UL 94 V2
<b>Operating Temperatures</b>	Maximum continuous 75°C, minimum -40°C (w/o impact).
<b>M Drawings</b>	<a href="#">Click here for M-Drawing</a>
<b>Catalog Page</b>	<a href="#">Click here for catalog page A22</a>
<b>Brochures</b>	<a href="#">Click here for product brochure</a>
<b>Catalog Section</b>	<a href="#">Click here for Section-A</a>
<b>UPC Number</b>	78358501316
<b>Weight in LBs</b>	0.15



NEMA 5-20P  
**20A 125V**  
UL CSA  
1 HP


NEMA  
Configuration



## Straight Blade Devices

**2 Pole, 3 Wire Grounding**

15 and 20 Ampere, 125 Volts

**VALISE® Plugs and Connector Bodies****HBL5965VY****HBL5966VBLK****HBL8115V****HBL5969VY****HBL5963VY****HBL8119V****IP20**  
SUITABILITYNEMA 5-15P  
15A 125V  
UL CSA  
0.5 HPNEMA 5-20P  
20A 125V  
UL CSA  
1 HP**Valise Plugs**

Description	Cord Dia.	Catalog Numbers	
Yellow nylon.	.220"-.660" (5.6-16.8)	<b>HBL5965VY</b>	<b>HBL5364VY</b>
Black nylon.	.220"-.660" (5.6-16.8)	<b>HBL5965VBLK</b>	<b>HBL5364VBK</b>
Gray nylon.	.220"-.660" (5.6-16.8)	<b>HBL5965VGY</b>	-
Insulation displacement terminals, black nylon.	.230"-.360" (5.8-9.1)	<b>HBL5966VBLK</b>	-
Insulation displacement terminals, yellow nylon.	.230"-.360" (5.8-9.1)	<b>HBL5966VY</b>	-

**Valise Hospital Grade Plugs**

Description	Cord Dia.	Catalog Numbers	
White nylon.	.300"-.660" (7.6-16.8)	<b>HBL8115V</b>	<b>HBL8364V</b>
Insulation displacement terminals, white nylon.	.230"-.360" (5.8-9.1)	<b>HBL8013V</b>	-

*Note: See Section I for complete line of hospital grade devices.***IP20**  
SUITABILITYNEMA 5-15R  
15A 125V  
UL CSANEMA 5-20R  
20A 125V  
UL CSA**Valise Connector Bodies**

Description	Cord Dia.	Catalog Numbers	
Yellow nylon.	.220"-.660" (5.6-16.8)	<b>HBL5969VY</b>	<b>HBL5369VY</b>
Black nylon.	.220"-.660" (5.6-16.8)	<b>HBL5969VBLK</b>	<b>HBL5369VBK</b>
Gray nylon.	.220"-.660" (5.6-16.8)	<b>HBL5969VGY</b>	-
Insulation displacement terminals, black nylon.	.230"-.360" (5.8-9.1)	<b>HBL5963VBK</b>	-
Insulation displacement terminals, yellow nylon.	.230"-.360" (5.8-9.1)	<b>HBL5963VY</b>	-

**Valise Hospital Grade Connector Body**

Description	Cord Dia.	Catalog Number	
White nylon.	.300"-.660" (7.6-16.8)	<b>HBL8119V</b>	-