



HBL5865VY -- Valise Plug




2P2W, 15A 125V, 1-15P, Non-Polarized, Yellow Nylon

Product Specifications

Product Type	 <p>Plugs</p>
Body Style	Straight
Standard	NEMA
Amperage	15A
Voltage	125V
Poles and Wires	2 Pole, 2 Wire Non-Grounding
Hospital Grade ?	No
Plug/Connector Grade	Valise
Enhancement	Un Polarized
Color	 <p>Yellow</p>
NEMA No.	1-15P
Horsepower	0.5
Cord Dia.	.218"-.385" (5.5-9.8)

Description	Straight Blade Plug
Type	2 Pole, 2 Wire, Non-Grounding
Rating	15A,125V
Certification	UL CSA
IP Suitability	IP20
Housing Material	Nylon
Cord Clamp Material	Noryl (Polyphenylene Oxide)
Contact Blades Material	.060" (1.5) Brass
Ground Contact Blade Material	.040" (1.0) Brass
Terminal Screw Material	Steel (copper finish)
Ground Screw Material	Steel (green finish)
Wire Clamps Material	.062" (1.8) Steel-nickel finish
Cable Inserts Material	Poly Phenylene Oxide
Body Holding Screws	Steel Multiple Drive
Dielectric Voltage	Withstands 2,000V minimum.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%..
Terminal Identification	Terminals identified in accordance with UL498 (Brass, White, Green).
Terminal Accommodation	#18-#14 AWG copper stranded or solid conductor only.
Product Identification	Ratings are a permanent part of the device.
Flammability	UL 94 V2.
Operating Temperatures	Maximum continuous 75°C, minimum -40°C (w/o impact).
M Drawings	Click here for M-Drawing
Catalog Page	Click here for catalog page A4
Brochures	Click here for product brochure
Catalog Section	Click here for Section-A
UPC Number	78358501306
Weight in LBs	0.15

 <p>NEMA 1-15P 15A 125V LL CSA 0.5 HP</p>
NEMA Configuration



Straight Blade Devices


2 Pole, 2 Wire Non-Grounding

15 and 20 Ampere, 125 and 250 Volts

Plugs, Connector Body and Receptacles




HBL5865VY



HBL5869VY



HBL9758VY



HBL5552B



IP20
SUITABILITY



NEMA 1-15P
15A 125V
UL CSA
0.5 HP



NEMA 1-15R
15A 125V
UL CSA

Valise® Plugs 15A, 125V

Description	Cord Dia.	Catalog Numbers
Yellow nylon, non-polarized.	.218"-.385" (5.5-9.8)	HBL5865VY -
Yellow nylon, polarized.	.218"-.385" (5.5-9.8)	HBL5866VY -

Valise Connector Body

Description	Cord Dia.	Catalog Number
Yellow nylon.	.218"-.385" (5.5-9.8)	- HBL5869VY



IP20
SUITABILITY



NEMA 2-20P
20A 250V
UL Listed
2 HP



NEMA 2-20R
20A 250V
UL Listed
2 HP

20A, 250V

Description	Cord Dia.	Catalog Numbers
Valise plug, yellow nylon.	.220"-.660" (5.6-16.8)	HBL9758VY -
Receptacle, single, black phenolic.		- HBL5552B

Note: Horsepower ratings are AC only and apply to plugs and receptacles only.