

HBL7485V -- Twist-Lock Valise Plug



3P3W, 15A 125/250V, ML-3P, Black Nylon Body


Product Specifications

Product Type



Product Item	Plug
Wiring Scheme	3 Pole, 3 Wire Non-Grounding
Amperage	15A
Voltage	125/250V AC
NEMA Configuration	ML-3P
Item Style	Valise
Device Color	Black
Cord Dia.	.300"-.430" (7.6-10.9)
Blade Holder Material	Black Nylon
Housing Material	Black nylon
Cord Clamp Material	Nylon
Blade Material	Brass
Terminal Clamp Material	Cold rolled steel-nickel-plated
Cord Clamp Screw Material	Steel zinc plated

Body Holding Screw Material	Steel zinc plated
Ratings	Molded into face
Dielectric Voltage Withstand	2,000 minimum
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30 C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
Terminal Accommodation	15A-#14AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, White)
Flammability	HB or better per UL 94 or CSA 22.2 No. 0.6
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Moisture Resistance	IP20
Listings	UL
Catalog Page	Click here for catalog page B34
Brochures	Click here for product brochure
Hubbellnet	Click here for Hubbellnet
Catalog Section	Click here for Section-B
UPC Number	78358523743
Weight in LBs	0.1




TWIST-LOCK® Devices


3 Pole, 3 Wire, Non-Grounding

15 Ampere, 125/250 Volts

Midget TWIST-LOCK Flanged Receptacles and Plugs



HBL7487N



HBL7487




HBL7489



HBL7485V



HBL7485



HBL7432



HBL7495V



Flanged Receptacles

Description	Catalog Numbers
Exposed terminals, black nylon flange.	HBL7487N
Exposed terminals, stainless steel flange,	HBL7487 -
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in diameter.	HBL7489 -

Male Plugs IP20 SUITABILITY

Description	Cord Dia.	Catalog Numbers
Valise® plug, black nylon, with insulation displacement terminals, multiple drive screws.	.300"-.430" (7.6-10.9)	- HBL7485V
Black nylon body, phenolic base, multiple drive screw terminals, cord grip.	.281"-.421" (7.1-10.7)	- HBL7485
Same as above, except angle cord grip.	.335"-.421" (8.5-10.7)	- HBL7432

Weatherproof Boot IP55** SUITABILITY

Description	Catalog Number
Seal-Tite® cover, black elastomer, for use with a HBL7485V or HBL7485 plug when used with a HBL7484V or HBL7484 connector body when used with a flanged inlet.	HBL7495V

*Notes: These devices are not interchangeable with any other devices in this catalog. All male ground pins are solid and all female ground contacts have hollow sleeves. **When installed and used properly with plug and connector body combinations. * Not UL Listed.*