


SHC1027 -- Straight Male Cord Connectors



Machined Aluminum

Machined Aluminum

Product Specifications

| | |
|-------------------------------------|--|
| <p>Product Type</p> |  <p>Accessories</p> |
| <p>Accessory Item</p> | <p>Straight Male Cord Connectors</p> |
| <p>NPT Size</p> | <p>1/2" NPT</p> |
| <p>Cord Crip Cable Range</p> | <p>.63" - .75"</p> |
| <p>Material</p> | <p>Machined Aluminum</p> |
| <p>Ingress Protection</p> | <p>IP66</p> |
| <p>Operating Temperature</p> | <p>-40° F to 300° F (-40° C to 149° C)</p> |
| <p>Hazardous Locations</p> | <p>Hubbell cord connectors are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC.</p> |
| <p>Certifications</p> | <p>UL Listed in Accordance with Standard 514B, CSA Certified, United States Coast Guard Approved, Title 46-Part 111</p> |
| <p>M Drawings</p> | <p>Click here for M-Drawing</p> |
| <p>Brochures</p> | <p>Click here for product brochure</p> |
| <p>Catalog Page</p> | <p>Click here for catalog page G74</p> |

| | |
|-----------------|--|
| Catalog Section | Click here for Section-G |
| UPC Number | 78358520027 |
| Weight in LBs | 0.15 |

