



International Components Corporation

Tel: 631-952-9595 • 800-645-9154 • Fax: 631-952-9597 • Email: oemsales@icc107.com



SUB-MINIATURE LOW PROFILE ROUND SPEAKERS

Part Number: SR800RMF

MODEL NUMBER	SR800RMF
FRAME DIAMETER (MM)	20
FRAME DEPTH (MM)	8.9
MATERIAL - CONE / FRAME	MYLAR / ABS
MAGNET TYPE	FERRITE
MAGNET: SIZE (MM) - WEIGHT (OUNCES/GRAMS)	16 x 7 x 5 -
RATED POWER (WATTS): Nom. / Max.	0.1 / 0.2
VOICE COIL IMPEDANCE (OHMS)	8 ± 15%
RESONANT FREQUENCY (Hz) Without Baffle	680 ± 20%
FREQUENCY RESPONSE (Hz)	F₀ - 5500
OUTPUT SOUND PRESSURE LEVEL (S.P.L.)	77 ± 10 dB
MEASURED AT:	1W @ 1M
MEAN VALUE AT:	1.0, 1.2, 1.5, 2.0K Hz
OPERATION (MUST BE NORMAL)	PROGRAM SOURCE 0.1W
BUZZ & RATTLES (MUST BE NORMAL)	0.89V SINE WAVE
DISTORTION @ RATED POWER INPUT	10% MAXIMUM @ 1,500 Hz
LOAD TEST (WHITE NOISE)	0.89 V 5 HRS
HUMIDITY TEST	N/A

HEAT TEST	N/A
OUTSIDE DIAMETER OF YOKE SEAT (MM)	14 - VOICE COIL = 5.9
OUTSIDE DIAMETER (ELIMINATE RIM)	N/A
BAFFLE OPENING (MM)	19
THICKNESS OF RIM (MM)	2.8
NET WEIGHT (OUNCES/GRAMS)	0.26 / 7.4

**POLARITY:
DIAPHRAGM SHALL MOVE FORWARD WHEN APPLYING A POSITIVE DC CURRENT TO THE "+" (OR MARKED) TERMINAL.**

***SPEAKER MUST MEET NORMAL OPERATION AND BUZZ & RATTLES SPECIFICATIONS**

■ DIMENSIONS

■ TYPICAL FREQUENCY RESPONSE CURVE

[Return to top](#)