

[view cart](#)

[View Cart](#)

[Downloads](#)

[Tracking](#)

[Home](#)

Part # :

it

Sales Support: 1-888-971-9888

[ROHS](#)

[secure online transactions](#)

*Hablamos Español*

Sun, Oct 28, 2007

[Applications](#)

[FAQs](#)

[Company](#)

[Catalog](#)

[Product News](#)

[Contact Us](#)

[Programmable Automation  
Controllers](#)

[Embedded / PLC Controllers](#)

[Data Acquisition](#)

[Industrial Data Communications](#)

[Industrial Touch LCD Monitors](#)

[Industrial Wireless Products](#)

[Power Supplies](#)

[Industrial Enclosures](#)

[Signal Conditioners](#)

[Quick Start Kits](#)

[Control & HMI Software](#)

[Product Support &  
Documentation](#)

## I-7510



### Product Reference & Support :

- [User's Manual](#)
- [Hardware](#)
- [FAQs](#)
- [Certifications](#)



### RS-485 Isolated High Speed Repeater

#### I-7510

#### Features

RS-485 isolated high speed repeater

#### Specifications & Additional Information

- **Input:** RS-485 protocol (two wire)
- **Output:** RS-485 protocol (two wire)
- **Speed:** "Self Tuner" inside  
Auto switching baud rate: 300 ~ 115200 bps
- **Isolation voltage:** 3000Vdc
- **Power consumption:** 2.2W max.

