

[view cart](#)

[View Cart](#)

[Downloads](#)

[Tracking](#)

[Home](#)

Part # :

it

Sales Support: 1-888-971-9888

[ROHS](#)

[secure online transactions](#)

Hablamos Español

Sun, Oct 28, 2007

Applications

FAQs

Company

Catalog

Product News

Contact Us

Programmable Automation
Controllers

Embedded / PLC Controllers

Data Acquisition

Industrial Data Communications

Industrial Touch LCD Monitors

Industrial Wireless Products

Power Supplies

Industrial Enclosures

Signal Conditioners

Quick Start Kits

Control & HMI Software

Product Support & Documentation

I-7520A



Product Reference & Support :

- [Manual](#)
- [Hardware](#)
- [Certification](#)
- [FAQs](#)
- [MTBF Report](#)



RS-232 to RS-422/RS-485 Converter

I-7520A

Features

RS-232 to RS-422/RS-485 converter

Specifications & Additional Information

- Output: RS-485/RS-422 protocol
- Speed: "Self Tuner" inside, auto switching baud rate, 300~115200 BPS
- 256 modules max. in one RS-485 network without repeater
- 2048 modules max. in one RS-485 network with repeater
- Isolation voltage: 3000VDC
- Repeater request: 4,000 feet or over 256 modules
- Input power : 12VDC ~ 24VDC
- Power consumption: 2.2W max.
- ROHS compliant product
- Din Rail Mount