

# Stripmaster Wire Stripper #20 to #30 AWG

Catalog # 45-098




## **Features**

- Knife-type blades
- Cleanly strips wire up to 7/8 in. (22mm)
- One-third less hand pressure for each strip
- Eliminates nicking, cutting, and fraying of wire
- Wire gripper holds wire centered in hole




Stripmaster® and Stripmaster® Lite **Wire Strippers** 

- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision-ground, knife-type blades provide clean, accurate stripping
- Sturdy die cast frame provides long-term durability
- Wire gripper holds wire securely in position
- Stripmaster® Lite designed for smaller hands 3/4 the size of the standard Stripmaster®



Wire Stripper



Gripper holds the wire securely in position.



Knife-type stripping blades have form-ground holes which penetrate the insulation like a knife, giving a clean insulation

#### Stripmaster® Wire Strippers and **Knife-Type Blades**



Specifications — Stripping Hole Diameter (Inches) Replacement Wire Size AWG Blades (Pair) 22 26 28 30 Cat. No. Cat. No. 12 20 45-090\* or 45-290\*\* .159 .141 .106 L-4419 .144 .105 .085 .073 .073 45-091 L-4420 .144 .113 .090 .072 .061 .048 .048 45-092\* or 45-292\*\* L-4421 .090 .072 .061 .039 .039 45-093 L-4422 L-4453 .230 .198 45-096 .072 .061 .048 .039 .032 .026 45-097 L-4994 .039 .026 .016 45-098 L-5361 .048 .032 .021 .198 .167 .062 .055 45-099 L-8763

Wire Stripper

\*Boxed \*\*Blister Card Tolerances +.001 -.005

#### Stripmaster® Lite Wire Strippers and Knife-Type Blades

Specifications — Stripping Hole Diameter (Inches) Wire Size AWG										Replacement				
12	14	16	18	20	Wir 22	e Size A 24	wu 26	28	30	16/18	20/22	Cutting Edge	Cat. No.	Blades (Pair) Cat. No.
		.072	.061	.048	.039								45-671	LB-1001
						.032	.026	.021	.016				45-672	LB-1002
.113	.090	.072	.061 (All Stranded wire)										45-673	LB-1003
.096	.085	.073		.061 (12 & 14 Solid wire, 16 & 18 Stranded wire)					45-674	LB-1004				
										.072	.048	.250 Wide	45-675	LB-1005

Tolerances +.001 -.005





Description	Coax Cable Type (RGU)	Repl. Blade Cat. No.	Cat. No.
Coax Stripmaster® for RG-6	RG-6	LB-740	45-262
Coax Stripmaster® for RG-58	RG-58	LB-742	45-264
Coax Stripmaster® for RG-59	RG-59	LB-743	45-265
Coax Stripmaster® for RG-62	RG-62	LB-744	N/A
Coax Stripmaster® for RG-6 QuadShield	RG-6 QuadShield	LA-3953	45-282

Coaxial Cables: two-step strip for termination, jacket and dielectric.

Replacement Frame Assemblies	Cat. No.
For Stripmaster® Wire Strippers	L-5620
For Stripmaster® Lite Wire Strippers	LB-1421

### Stripmaster® Wire Strippers with Rectangular Holes



Description	Cat. No.	Replacement Blades (Pair) Cat. No.
For Flat Telephone Cable (.60 in. or 1.52mm)	N/A	LB-1155
For European Flat Lamp Cord	45-089	L-8762
For SP-SPT Lamp Cord	45-095*	L-4452

<sup>\*</sup>Also strips 2- and 3-conductor low-voltage wire used in G.E. and Touchplate remote control wiring system.

Optional Accessories	Cat. No.
Transparent Adjustable Wire Stop (for Stripmaster® Wire Strippers)	L-5270
Transparent Adjustable Wire Stop (for Stripmaster® Lite Wire Strippers)	LB-1195
Replacement Moveable Gripper	L-1953