

Stripmaster Lite Wire Stripper, #24 to #30 AWG

Catalog # 45-672



Features

- Knife-type blades
- Cleanly strips wire up to 7/8 in. (22mm)
- Requires one third less hand pressure for each strip
- Eliminates nicking, cutting, and fraying of wire
- Wire gripper holds wire centered in hole



Stripmaster[®] and Stripmaster[®] Lite Wire Strippers

- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision-ground, knife-type blades provide clean, accurate stripping
- Sturdy die cast frame provides long-term durability
- Wire gripper holds wire securely in position
- Stripmaster[®] Lite designed for smaller hands 3/4 the size of the standard Stripmaster[®]

Stripmaster® Wire Strippers and Knife-Type Blades





MUMDOUN

And And



Knife-type stripping blades have form-ground holes which penetrate the insulation like a knife, giving a clean insulation

Gripper holds the wire

securely in position.

| Specifications — Stripping Hole Diameter (Inches) | | | | | | | | | | Replacement Blades (Pair) | | | |
|---|------|---------------------------------|--|----------------------------------|---|---|--|---|--|--|--|---|--|
| Wire Size AWG | | | | | | | | | | | | | |
| 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | 28 | 30 | Cat. No. | Cat. No. |
| .159 | .141 | .106 | | | | | | | | | | 45-090* or 45-290** | L-4419 |
| | .144 | .105 | .085 | .073 | .073 | | | | | | | 45-091 | L-4420 |
| | .144 | .113 | .090 | .072 | .061 | .048 | .048 | | | | | 45-092* or 45-292** | L-4421 |
| | | | .090 | .072 | .061 | .039 | .039 | | | | | 45-093 | L-4422 |
| .198 | | | | | | | | | | | | 45-096 | L-4453 |
| | | | | .072 | .061 | .048 | .039 | .032 | .026 | | | 45-097 | L-4994 |
| | | | | | | .048 | .039 | .032 | .026 | .021 | .016 | 45-098 | L-5361 |
| .198 | .167 | | | .062 | .055 | | | | | | | 45-099 | L-8763 |
| .1 | 159 | 159 .141 .144 .144 198 | 159 .141 .106 .144 .105 .144 .113 .148 .113 .198 | 8 10 12 14 159 .141 .106 | 8 10 12 14 16 159 .141 .106 .144 .105 .085 .073 .144 .113 .090 .072 .144 .113 .090 .072 198 | 8 10 12 14 16 18 159 .141 .106 - - .144 .105 .085 .073 .073 .144 .105 .085 .073 .073 .144 .113 .090 .072 .061 198 - - - - 198 - .073 .072 .061 | 8 10 12 14 16 18 20 159 .141 .106 | 8 10 12 14 16 18 20 22 159 .141 .106 <t< td=""><td>8 10 12 14 16 18 20 22 24 159 .141 .106 </td><td>8 10 12 14 16 18 20 22 24 26 159 .141 .106 <</td><td>8 10 12 14 16 18 20 22 24 26 28 159 .141 .106 <t< td=""><td>8 10 12 14 16 18 20 22 24 26 28 30 159 .141 .106 <t< td=""><td>8 10 12 14 16 18 20 22 24 26 28 30 Cat. No. 159 .141 .106 </td></t<></td></t<></td></t<> | 8 10 12 14 16 18 20 22 24 159 .141 .106 | 8 10 12 14 16 18 20 22 24 26 159 .141 .106 < | 8 10 12 14 16 18 20 22 24 26 28 159 .141 .106 <t< td=""><td>8 10 12 14 16 18 20 22 24 26 28 30 159 .141 .106 <t< td=""><td>8 10 12 14 16 18 20 22 24 26 28 30 Cat. No. 159 .141 .106 </td></t<></td></t<> | 8 10 12 14 16 18 20 22 24 26 28 30 159 .141 .106 <t< td=""><td>8 10 12 14 16 18 20 22 24 26 28 30 Cat. No. 159 .141 .106 </td></t<> | 8 10 12 14 16 18 20 22 24 26 28 30 Cat. No. 159 .141 .106 |

MARION

Stripmaster[®]

Wire Stripper

ed **Blister Card Tolerances +.001 -.005

Stripmaster® Lite Wire Strippers and Knife-Type Blades

| Specifications — Stripping Hole Diameter (Inches) Wire Size AWG | | | | | | | | | | | Replacement Blades (Pair) | | | |
|--|------|------|--|-------------|----------|------|------|------|------|--------|------------------------------|--------------|----------|----------|
| 12 | 14 | 16 | 18 | 20 | 22 | 24 | 26 | 28 | 30 | 16/18 | 20/22 | Cutting Edge | Cat. No. | Cat. No. |
| | | .072 | .061 | .048 | .039 | | | | | | | | 45-671 | LB-1001 |
| | | | | | | .032 | .026 | .021 | .016 | | | | 45-672 | LB-1002 |
| .113 | .090 | .072 | .061 (A | All Strande | ed wire) | | | | | | | | 45-673 | LB-1003 |
| .096 | .085 | .073 | .061 (12 & 14 Solid wire, 16 & 18 Stranded wire) | | | | | | | 45-674 | LB-1004 | | | |
| | | | | | | | | | | .072 | .048 | .250 Wide | 45-675 | LB-1005 |

Tolerances +.001 -.005

$\textbf{Coax Stripmaster}^{\circledast} \textbf{ Wire Strippers and Blades}$

| Description | Coax Cable Type (RGU) | Repl. Blade Cat. No. | Cat. No. |
|---------------------------------------|--------------------------|-------------------------|----------|
| Coax Stripmaster® for RG-6 | RG-6 | LB-740 | 45-262 |
| Coax Stripmaster® for RG-58 | RG-58 | LB-742 | 45-264 |
| Coax Stripmaster® for RG-59 | RG-59 | LB-743 | 45-265 |
| Coax Stripmaster® for RG-62 | RG-62 | LB-744 | N/A |
| Coax Stripmaster® for RG-6 QuadShield | RG-6 QuadShield | LA-3953 | 45-282 |

Coaxial Cables: two-step strip for termination, jacket and dielectric.

| Replacement Frame Assemblies | Cat. No. |
|--------------------------------------|----------|
| For Stripmaster® Wire Strippers | L-5620 |
| For Stripmaster® Lite Wire Strippers | LB-1421 |

Stripmaster[®] Wire Strippers with Rectangular Holes



| Description | Cat. No. | Replacement Blades (Pair) Cat. No. |
|---|----------|--|
| For Flat Telephone Cable (.60 in. or 1.52mm) | N/A | LB-1155 |
| For European Flat Lamp Cord | 45-089 | L-8762 |
| For SP-SPT Lamp Cord | 45-095* | L-4452 |

*Also strips 2- and 3-conductor low-voltage wire used in G.E. and Touchplate remote control wiring system.

| Optional Accessories | Cat. No. |
|---|----------|
| Transparent Adjustable Wire Stop (for Stripmaster® Wire Strippers) | L-5270 |
| Transparent Adjustable Wire Stop (for Stripmaster® Lite Wire Strippers) | LB-1195 |
| Replacement Moveable Gripper | L-1953 |