




**E-Chain E2 Micro: 06-10-028-0 Inch Version**

Inner Width	Outer Width	Radius	Curve Height H	Curve Length K	Weight
0.39 in	0.65 in	1.10 in	2.83 in	5.51 in	0.09 lbs/ft

Operating Space: H + .4" @ .135 lbs/ft



8 Widths  
3 Bending Radii



Mounting brackets with or without strain relief tiewrap plate




**Quicksnap:** the complete unit, detachable by hand  
Call for availability



**Quickfix:** mounting bracket with pin  
Call for availability




High torsional rigidity



Unsupported length

- $FL_B$  = unsupported with permitted sag
- $FL_G$  = unsupported with straight upper run



**Product Range:**

Inner Widths (Bi) inches (mm):	.24 (6), .39 (10), .63 (16), .79 (20), 1.18 (30), 1.57 (40), 1.97 (50), 2.52 (64)
Bending Radii (R) inches (mm):	.71 (018), 1.10 (028), 1.50 (038)
Pitch:	.79 (20 mm/link) = 15.24 links/ft (50 links/m)



**When to use the Series 06 E2 "micro":**


- If high torsional rigidity is required
- If cost is a factor
- If connection options are required (Quicksnap, Quickfix, etc.)



**When not to use the Series 06 E2 "micro":**

- If snap-open links are required
- If quick insertion of cables with pre-assembled connectors is necessary


# Series 06 E2 "micro"



Part No.	Bi	Ba
06-06	.24 (6)	.49 (12.5)
06-10	.39 (10)	.65 (16.5)
06-16	.63 (16)	.89 (22.5)
06-20	.79 (20)	1.06 (27)
06-30	1.18 (30)	1.46 (37)
06-40	1.57 (40)	1.85 (47)
06-50	1.97 (50)	2.24 (57)
06-64	2.52 (64)	2.80 (71)

Bending Radii  
for ALL Widths  
.71 (018)  
1.10 (028)  
1.50 (038)

## Installation Dimensions



R	.71 (018)	1.10 (028)	1.50 (038)
H*	2.05 (52)	2.83 (72)	3.62 (92)
D	1.77 (45)	2.17 (55)	2.56 (65)
K	3.94 (100)	5.51 (140)	6.30 (160)



\*The required clearance height is  $H_F = H + .39$  (10) with .13 lbs/ft (0.2 kg/m) fill weight.

Pitch: = .79 (20 mm) per link  
 Links per ft (m): = 15.24 (50)  
 Chain length: =  $\frac{S}{2} + K$

## Mounting Brackets

### Polymer, One Piece

- One-piece, locked mounting bracket
- Corrosion resistant
- Available pre-assembled
- Inner and outer attachment possible
- Available with strain relief tiwrap plates




060-06-12 - 060-20-12:  
Center bores only  
 060-30-12 - 060-64-12:  
Outer bores only


Chain Type	Part No. Full set with Tiwrap Plate	Part No. Mounting Bracket Set	Number of Teeth	Dimension A in. (mm)	Dimensions B in. (mm)
06-06	060-06-12 PZ	060-06-12	1	-	.49 (12.5)
06-10	060-10-12 PZ	060-10-12	1	-	.65 (16.5)
06-16	060-16-12 PZ	060-16-12	2	-	.89 (22.5)
06-20	060-20-12 PZ	060-20-12	2	-	1.06 (27.0)
06-30	060-30-12 PZ	060-30-12	3	.87 (22)	1.46 (37.0)
06-40	060-40-12 PZ	060-40-12	4	1.26 (32)	1.85 (47.0)
06-50	060-50-12 PZ	060-50-12	5	1.65 (42)	2.24 (57.0)
06-64	060-64-12 PZ	060-60-12	6	2.20 (56)	2.80 (71.0)

06...12 = Full set, each  
part with pin/bore  
 06... 1 = Mounting bracket  
with bore  
 06... 2 = Mounting bracket  
with pin

## Order example



## 06-20...




### 1. Chain selection:

06-20-038-0



### 2. Mounting brackets:

060-20-12 PZ - with strain relief tiewrap plates



For 16.4 ft (5 m) chain, color black, with mounting brackets:

16.4 ft (5 m) 06-20-038-0 and 060-20-12 PZ



## Technical data

Chain Type	Weight Per Link		Weight	
	(oz.)	(g)	(lbs/ft)	(kg/m)
06-06	0.091	(≈ 2.6)	0.087	(≈ 0.13)
06-10	0.098	(≈ 2.8)	0.094	(≈ 0.14)
06-16	0.112	(≈ 3.2)	0.107	(≈ 0.16)
06-20	0.119	(≈ 3.4)	0.114	(≈ 0.17)
06-30	0.140	(≈ 4.0)	0.134	(≈ 0.20)
06-40	0.161	(≈ 4.6)	0.155	(≈ 0.23)
06-50	0.182	(≈ 5.2)	0.175	(≈ 0.26)
06-64	0.210	(≈ 6.0)	0.202	(≈ 0.30)

Material	igumid G
Permitted temperature	-40°F/266°F (-40°C/+130°C)
Gliding speed max.	16.4 ft/s (5 m/s)
Unsupported v max.	32.81 ft/s (10 m/s)
Flammability class	VDE 0304 IIC UL94 HB