Adjustable Precision Wire Strippers

These Precision Wire Strippers feature an adjustment dial that allows the operator to select one of six different settings.

A calibrated wire stop can then be adjusted for the desired insulation strip length. In a single motion, the operator squeezes and pulls the tool. This action engages four specially hardened blades to cleanly cut the wire insulation while the pulling motion breaks the insulation / conductor bond.



Adjustable to six wire gauges:
ST-450 26 to 36 AWG
ST-500 20 to 30 AWG
ST-500ESD 20 to 30 AWG
ST-550 18 to 28 AWG
Calibrated Wire Stop adjustable to 2" (50.8mm)
Clean, precise strip of any insulation type
Lightweight-weighs 1 oz.
Blade is hardened steel (RC58)
Dimensions 3.9" x 1.6" x 0.6"
(99 mm x 42 mm x 14 mm)

INCHES	METRIC				
Part No.		ST-450	ST-500	ST-500ESD	ST-550
Wire Gauge		26-36 AWG	20-30 AWG	20-30 AWG	18-28 AWG
Calibrated Wire Strip Length		Adjustable to 2"	Adjustable to 2"	Adjustable to 2"	Adjustable to 2"
Insulation Type		Any	Any	Any	Any
Dimensions (L x H x Thickness)		3.9' x 1.6" x 0.6'	3.9" x 1.6" x 0.6"	3.9" x 1.6' x 0.6'	3.9" x 1.6" x 0.6"
Housing Material		ABS	ABS	ESD Safe Polycarbonate	ABS
Blade		Hardened Steel (RC 58)	Hardened Steel (RC 58)	Hardened Steel (RC 58)	Hardened Steel (RC 58)