#### Deluxe Molded D-sub Cable, HD26 Male / Female, 2.5 ft

#### Features for this product

- Wired straight through for extending serial devices/peripherals
- 360 degree fully shielded for protection against EMI/RFI
- Gold plated contacts provide reliable connections with repeated mating cycles
- Hex nuts on female connectors are removable to expose 4-40 thumb screws
- HDB26 male to female connectors; lengths range from 2.5 ft to 50 ft; color is light gray



L-com's CHD26 family of hard to find high density D-sub cable assemblies offer solid performance at economical prices. Fully shielded throughout the entire cable to prevent against data corrupting EMI/RFI. Molded backshells provide superior strain relief while robust 26 AWG conductors are wired straight through for ease of compatibility. Metal thumbscrews insure fast and easy connections. Custom lengths and pinouts are available with modest minimum requirements.

#### Details for this D-Subminiature product

L-com Item # CHD26MF-2.5

Manufacturer L-com

UPC # 822335010277

RoHS Status Partially RoHS Compliant Stock



Item # Description

# Deluxe High-Density 15 Pin D-Sub Cables - Fully Populated and Completely Shielded

High-density D-Sub connectors are used in a number of PC and network applications. This type of connector can usually be recognized because they have three rows of smaller pins versus the larger pins used in conventional D-Subs. Fully populated with stranded conductors and aluminum mylar shielding. Hex nuts on female connectors are removable to expose 4-40 thumbscrews.

```
CHD15MM-2.5
                            Deluxe Molded Cable, HD15 Male / Male, 2.5 ft
CHD15MM-5
                            Deluxe Molded Cable, HD15 Male / Male, 5.0 ft
CHD15MM-7.5
                            Deluxe Molded Cable, HD15 Male / Male, 7.5 ft
CHD15MM-10
                            Deluxe Molded Cable, HD15 Male / Male, 10.0 ft
CHD15MM-15
                            Deluxe Molded Cable, HD15 Male / Male, 15.0 ft
CHD15MM-25
                            Deluxe Molded Cable, HD15 Male / Male, 25.0 ft
CHD15MF-2.5
                            Deluxe Molded Cable, HD15 Male / Female, 2.5 ft
CHD15MF-5
                            Deluxe Molded Cable, HD15 Male / Female, 5.0 ft
                            Deluxe Molded Cable, HD15 Male / Female, 7.5 ft
CHD15MF-7.5
CHD15MF-10
                            Deluxe Molded Cable, HD15 Male / Female, 10.0 ft
CHD15MF-15
                            Deluxe Molded Cable, HD15 Male / Female, 15.0 ft
CHD15MF-25
                            Deluxe Molded Cable, HD15 Male / Female, 25.0 ft
```

Note: Most monitor manufacturers recommend using premium grade VGA cables that utilize 75 0hm coaxial lines.

# Deluxe High-Density 26 Pin Molded Cables - Ready Made, Fully Populated for Many Applications

Fully molded data cables equipped with high-density D-Sub connectors. Fully populated with 26AWG stranded conductors and aluminum mylar shielding. They are equipped with readily accessible thumbscrew type hold downs. Hex nuts on female connectors are removable to expose 4-40 thumbscrews.

```
CHD26MM-2.5
                           Deluxe Molded Cable, HD26 Male / Male, 2.5 ft
CHD26MM-5
                           Deluxe Molded Cable, HD26 Male / Male, 5.0 ft
CHD26MM-10
                           Deluxe Molded Cable, HD26 Male / Male, 10.0 ft
CHD26MM-15
                           Deluxe Molded Cable, HD26 Male / Male, 15.0 ft
CHD26MF-2.5
                           Deluxe Molded Cable, HD26 Male / Female, 2.5 ft
CHD26MF-5
                           Deluxe Molded Cable, HD26 Male / Female, 5.0 ft
CHD26MF-10
                           Deluxe Molded Cable, HD26 Male / Female, 10.0 ft
CHD26MF-15
                           Deluxe Molded Cable, HD26 Male / Female, 15.0 ft
                           Deluxe Molded Cable, HD26 Male / Female, 25.0 ft
CHD26MF-25
CHD26MF-50
                           Deluxe Molded Cable, HD26 Male / Female, 50.0 ft
```

# Deluxe High-Density 44 Pin Molded Cables - Fully Populated and Shielded

Injection molded cable assemblies with HD44 terminations. Fully populated with 24AWG stranded conductors and aluminum mylar and braided shielding. 4-40 metal thumbscrews molded into the strain relief. Hex nuts on female connectors are removable to expose 4-40 thumbscrews.

| CHD44MM-2.5 | Deluxe Molded Cable, HD44 Male / Male, 2.5 ft    |
|-------------|--|
| CHD44MM-5   | Deluxe Molded Cable, HD44 Male / Male, 5.0 ft    |
| CHD44MM-10  | Deluxe Molded Cable, HD44 Male / Male, 10.0 ft   |
| CHD44MM-15  | Deluxe Molded Cable, HD44 Male / Male, 15.0 ft   |
| CHD44MM-25  | Deluxe Molded Cable, HD44 Male / Male, 25.0 ft   |
| CHD44MM-50  | Deluxe Molded Cable, HD44 Male / Male, 50.0 ft   |
| CHD44MF-2.5 | Deluxe Molded Cable, HD44 Male / Female, 2.5 ft  |
| CHD44MF-5   | Deluxe Molded Cable, HD44 Male / Female, 5.0 ft  |
| CHD44MF-10  | Deluxe Molded Cable, HD44 Male / Female, 10.0 ft |
| CHD44MF-15  | Deluxe Molded Cable, HD44 Male / Female, 15.0 ft |
| CHD44MF-25  | Deluxe Molded Cable, HD44 Male / Female, 25.0 ft |
| CHD44MF-50  | Deluxe Molded Cable, HD44 Male / Female, 50.0 ft |

### Deluxe High-Density 62 Pin Molded Cables - 31 Twisted Pairs and Full Shielding

Fully molded data cables with HD62 D-Sub connectors. Fully shielded with aluminum mylar shielding and fully populated with 28AWG twisted pairs. Straight-thru pinning. Equipped with 4-40 thumbscrews. Hex nuts on female connectors are removable to expose 4-40 thumbscrews.

| CHD62MM-2.5              | Deluxe Molded Cable, HD62 Male / Male, 2.5 ft   |
|--------------------------|---|
| CHD62MM-5                | Deluxe Molded Cable, HD62 Male / Male, 5.0 ft   |
| CHD62MM-10               | Deluxe Molded Cable, HD62 Male / Male, 10.0 ft  |
| CHD62MM-15               | Deluxe Molded Cable, HD62 Male / Male, 15.0 ft  |
| CHD62MM-25               | Deluxe Molded Cable, HD62 Male / Male, 25.0 ft  |
| CHD62MM-50               | Deluxe Molded Cable, HD62 Male / Male, 50.0 ft  |
|                          |   |
| CHD62MF-2.5              | Deluxe Molded Cable, HD62 Male / Female, 2.5 ft   |
| CHD62MF-2.5<br>CHD62MF-5 | Deluxe Molded Cable, HD62 Male / Female, 2.5 ft<br>Deluxe Molded Cable, HD62 Male / Female, 5.0 ft  |
|                          |   |
| CHD62MF-5                | Deluxe Molded Cable, HD62 Male / Female, 5.0 ft   |
| CHD62MF-5<br>CHD62MF-10  | Deluxe Molded Cable, HD62 Male / Female, 5.0 ft<br>Deluxe Molded Cable, HD62 Male / Female, 10.0 ft |

### Deluxe High-Density 78 Pin Molded Cables - 39 Twisted Pairs and Double Shielded

Fully molded data cables equipped with HD78 D-Sub connectors. Fully shielded with aluminum mylar and braided shielding and fully populated with 28AWG twisted pairs. Straight-thru pinning, Equipped with 4-40 thumbscrews. Hex nuts on female connectors are removable to expose 4-40 thumbscrews.

```
CHD78MM-2.5
                           Deluxe Molded Cable, HD78 Male / Male, 2.5 ft
CHD78MM-5
                           Deluxe Molded Cable, HD78 Male / Male, 5.0 ft
CHD78MM-10
                           Deluxe Molded Cable, HD78 Male / Male, 10.0 ft
CHD78MM-25
                           Deluxe Molded Cable, HD78 Male / Male, 25.0 ft
CHD78MM-50
                           Deluxe Molded Cable, HD78 Male / Male, 50.0 ft
CHD78MF-2.5
                           Deluxe Molded Cable, HD78 Male / Female, 2.5 ft
CHD78MF-5
                           Deluxe Molded Cable, HD78 Male / Female, 5.0 ft
CHD78MF-10
                           Deluxe Molded Cable, HD78 Male / Female, 10.0 ft
CHD78MF-25
                           Deluxe Molded Cable, HD78 Male / Female, 25.0 ft
CHD78MF-50
                           Deluxe Molded Cable, HD78 Male / Female, 50.0 ft
```

