



We Tame Photons to Work for You!



Products

Search Tools

Solutions

Literature

Tech Notes

Support

Corporate

Products > LED Indicators > PCB Indicators > Assembled Housing > Round > 5mm > 2 Leaded > Quad Ranch

Features / Options

- ▶ Vertical Positioning
- ▶ Multi-Unit Construction
- ▶ Polarity Orientation Holder
- ▶ Choice of Colors and Lenses

Applications / Uses

- ▶ Board Level Status Indicators
- ▶ Board Level Fault Indicators
- ▶ Warning/Alarm Signaling
- ▶ Circuit Fault Finder Indicators



Part Number:	SPEC	Brightness	Material	Emitted Color	Wavelength	Intensity	View Angle	Voltage
SSF-LXH400GD		STANDARD	GaP	Green	565			2.1
SSF-LXH400HGW		STANDARD	GaP	Red/ Green	695/565			2.1
SSF-LXH400ID		STANDARD	GaAsP	Red	635			2.1
SSF-LXH400LGD		STANDARD	GaP	Green	565			1.8
SSF-LXH400LID		STANDARD	GaAsP	Red	635			1.8
SSF-LXH400LYD		STANDARD	GaAsP	Yellow	585			1.8
SSF-LXH400SID		HIGH	AllnGaP	Red	636	80	20	2.0
SSF-LXH400SID-1		HIGH	AllnGaP	Red	636	80	20	2.0
SSF-LXH400SOD		HIGH	AllnGaP	Orange	610	80	20	2.0
SSF-LXH400SOD-1		HIGH	AllnGaP	Orange	610	80	20	2.0
SSF-LXH400SRD		HIGH	GaAlAs	Red	660			1.7