

Power Distribution Blocks

600 Volts

Specifications:

- Connector, High Conductive Aluminum, Tin Plated
- Rated for Copper and Aluminum Wire
- Amp Rating Based on NEC Table 310-16 Using 75°C Copper Wire
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR19766
- CE
- For detailed SCCR information, please visit www.marathonsp.com



** Openings rated for #4-14 AWG are multiple wire rated: (2) #10 CU Str, (2 to 4) #12 CU Str, and (2 to 4) #14 CU Str.

*** Openings rated for #2-14 AWG are multiple wire rated: (2) #8 CU Str, (2) #10 CU Str, (2) #12 CU Str, and (2) #14 CU Str

Catalog #	Hinge Cover	Poles	Amps	Material	Connector Configuration	Line Wire Range	Openings Per Pole	Connector Configuration	Load Wire Range	Openings Per Pole
1411403 1412403 1413403 1414403		1 2 3 4	60	Thermoplastic		#2-#14 AWG	1		#10-#18 AWG	2
1411400 1412400 1413400 1414400		1 2 3 4	115	Thermoplastic		#2-#14 AWG	1		#10-#16 AWG	4
1320570 1321570 1322570 1323570	CH CH CH	Adder 1 2 3	175	Thermoplastic		2/0-#14 AWG	1		** #4-#14 AWG	4
1421570 1422570 1423570		1 2 3	175	Phenolic		2/0-#14 AWG	1		** #4-#14 AWG	4
1320580 1321580 1322580 1323580	CH CH CH	Adder 1 2 3	175	Thermoplastic		2/0-#14 AWG	1		** #4-#14 AWG	6
1402402 1403402		2 3	175	Phenolic		2/0-#14 AWG	1		** #4-#14 AWG	4
1402401 1403401		2 3	175	Phenolic		2/0-#14 AWG	1		** #4-#14 AWG	6
1402404 1403404		2 3	310	Phenolic		350 kcmil - #6 AWG	1		#4-#14 AWG	6
1331554 1332554 1333554	CH CH CH	1 2 3	310	Thermoplastic		350 kcmil - #6 AWG	1		#2/0-#14 AWG	2
1441401 1442401 1443401		1 2 3	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	6
1431552 1432552 1433552		1 2 3	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	4
1431553 1432553 1433553		1 2 3	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	6
1441560 1442560 1443560		1 2 3	335	Phenolic		400 kcmil - #6 AWG	1		#2-#14 AWG	8
1331552 1332552 1333552	CH CH CH	1 2 3	335	Thermoplastic		400 kcmil - #6 AWG	1		*** #2-#14 AWG	4

CH = Available with hinge cover attached
See pages 54-56 for dimensional information