

Power Distribution Blocks































600 Volts

Specifications:

- Connector, High Conductive Aluminum, Tin Plated
- Rated for Copper and Aluminum Wire
- Amp Rating Based on NEC Table 310-16 Using 75°C Copper Wire
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR19766
- CE
- For detailed SCCR information, please visit www.marathonsp.com

** Openings rated for #4-14 AWG are multiple wire rated:
(2) #10 CU Str, (2 to 4) #12 CU Str, and (2 to 4) #14 CU Str.

*** Openings rated for #2-14 AWG are multiple wire rated:
(2) #8 CU Str, (2) #10 CU Str, (2) #12 CU Str, And
(2) #14 CU Str

| Catalog # | Hinge Cover | Poles | Amps | Material | Connector Configuration | Line Wire Range | Openings Per Pole | Connector Configuration | Load Wire Range | Openings Per Pole |
|-----------|-------------|-------|------|---------------|---|----------------------|-------------------|---|--|-------------------|
| 1431555 | | 1 | 350 | Phenolic |  | #2/0-#14 AWG | 2 |  | ** #4-#14 AWG | 6 |
| 1432555 | | 2 | | | | | | | | |
| 1433555 | | 3 | | | | | | | | |
| 1331555 | CH | 1 | 350 | Thermoplastic |  | #2/0-#14 AWG | 2 |  | ** #4-#14 AWG | 6 |
| 1332555 | CH | 2 | | | | | | | | |
| 1333555 | CH | 3 | | | | | | | | |
| 1441551 | | 1 | 380 | Phenolic |  | 500 kcmil - #4 AWG | 1 |  | #2-#14 AWG | 6 |
| 1442551 | | 2 | | | | | | | | |
| 1443551 | | 3 | | | | | | | | |
| 1451579 | | 1 | 380 | Phenolic |  | 500 kcmil - #4 AWG | 1 |  | #2/0-#14 AWG | 6 |
| 1452579 | | 2 | | | | | | | | |
| 1453579 | | 3 | | | | | | | | |
| 1331587 | CH | 1 | 380 | Thermoplastic |  | 500 kcmil - #4 AWG | 1 |  | ***#2-#14 AWG 350 kcmil - #6 AWG | 3 |
| 1332587 | CH | 2 | | | | | | | | 1 |
| 1333587 | CH | 3 | | | | | | | | 1 |
| 1431587 | | 1 | 380 | Phenolic |  | 500 kcmil - #4 AWG | 1 |  | ***#2-#14 AWG 350 kcmil - #6 AWG | 3 |
| 1432587 | | 2 | | | | | | | | 1 |
| 1433587 | | 3 | | | | | | | | 1 |
| 1451594 | | 1 | 380 | Phenolic |  | 500 kcmil - #4 AWG | 1 |  | #2-#14 AWG | 8 |
| 1452594 | | 2 | | | | | | | | |
| 1453594 | | 3 | | | | | | | | |
| 1451552 | | 1 | 380 | Phenolic |  | 500 kcmil - #4 AWG | 1 |  | #2-#14 AWG | 12 |
| 1452552 | | 2 | | | | | | | | |
| 1453552 | | 3 | | | | | | | | |
| 1331588 | CH | 1 | 420 | Thermoplastic |  | 600 kcmil - #2 AWG | 1 |  | *** #2-14 AWG #1/0 - #14 AWG | 6 |
| 1332588 | CH | 2 | | | | | | | | 3 |
| 1333588 | CH | 3 | | | | | | | | 3 |
| 1331595 | CH | 1 | 420 | Thermoplastic |  | 600 kcmil - #2 AWG | 1 |  | ** #4-#14 AWG | 12 |
| 1332595 | CH | 2 | | | | | | | | |
| 1333595 | CH | 3 | | | | | | | | |
| 1331585 | CH | 1 | 420 | Thermoplastic |  | 600 kcmil - #2 AWG | 1 |  | *** #2-#14 AWG | 8 |
| 1332585 | CH | 2 | | | | | | | | |
| 1333585 | CH | 3 | | | | | | | | |
| 1331575 | CH | 1 | 420 | Thermoplastic |  | 600 kcmil - #2 AWG | 1 |  | 2/0-#14 AWG | 4 |
| 1332575 | CH | 2 | | | | | | | | |
| 1333575 | CH | 3 | | | | | | | | |
| 1331565 | CH | 1 | 420 | Thermoplastic |  | 600 kcmil - #2 AWG | 1 |  | 250 kcmil - #1/0 AWG | 2 |
| 1332565 | CH | 2 | | | | | | | | |
| 1333565 | CH | 3 | | | | | | | | |
| 1331596 | CH | 1 | 510 | Thermoplastic |  | 250 kcmil - #1/0 AWG | 2 |  | ** #4-#14 AWG | 12 |
| 1332596 | CH | 2 | | | | | | | | |
| 1333596 | CH | 3 | | | | | | | | |
| 1331597 | CH | 1 | 510 | Thermoplastic |  | 250 kcmil - #1/0 AWG | 2 |  | *** #2-#14 AWG | 8 |
| 1332597 | CH | 2 | | | | | | | | |
| 1333597 | CH | 3 | | | | | | | | |

CH = Available with hinge cover attached
See pages 54-57 for dimensional information

Power Blocks