





























Power Splicer Blocks

600 Volts

Specifications:

- Connector, High Conductive Aluminum, Tin Plated
- Rated for Copper and Aluminum Wire
- Amp Rating Based on NEC Table 310-16 Using 75°C and 90°C Copper Wire
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR19766
- CE
- For detailed SCCR information, please visit www.marathonsp.com



Catalog #	Hinge Cover	Poles	Amps	Material	Connector Configuration	Line Wire Range	Openings Per Pole	Connector Configuration	Load Wire Range	Openings Per Pole
1411300		1	115	Thermoplastic		#2 - #14 AWG	1		#2 - #14 AWG	1
1412300		2								
1413300		3								
1414300		4								
1421552		1	115	Phenolic		#2 - #14 AWG	1		#2 - #14 AWG	1
1422552		2								
1423552		3								
1320572	CH	Adder	175	Thermoplastic		#2/0 - #14 AWG	1		#2/0 - #14 AWG	1
1321572		1								
1322572		2								
1323572	CH	3								
1421572		1	175	Phenolic		#2/0 - #14 AWG	1		#2/0 - #14 AWG	1
1422572		2								
1423572		3								
1402801		2	255	Phenolic		250 kcmil - #6 AWG	1		250 kcmil - #6 AWG	1
1403801		3								
1431123		1	255	Phenolic		250 kcmil - #6 AWG	1		250 kcmil - #6 AWG	1
1432123		2								
1433123		3								
1402303		2	310	Phenolic		350 kcmil - #6 AWG	1		350 kcmil - #6 AWG	1
1403303		3								
1431126		1	310	Phenolic		350 kcmil - #6 AWG	1		350 kcmil - #6 AWG	1
1432126		2								
1433126		3								
1331126	CH	1	310	Thermoplastic		350 kcmil - #6 AWG	1		350 kcmil - #6 AWG	1
1332126		2								
1333126		3								
1331305	CH	1	350	Thermoplastic		#2/0 - #14 AWG	2		#2/0 - #14 AWG	2
1332305		2								
1333305		3								
1441557		1	420	Phenolic		600 kcmil - #4 AWG	1		600 kcmil - #4 AWG	1
1442557		2								
1443557		3								
1331360	CH	1	420	Thermoplastic		600 kcmil - #2 AWG	1		600 kcmil - #2 AWG	1
1332360		2								
1333360		3								
1331320	CH	1	510	Thermoplastic		250 kcmil - #1/0 AWG	2		250 kcmil - #1/0 AWG	2
1332320		2								
1333320		3								
1451129		1	620	Phenolic		350 kcmil - #4 AWG	2		350 kcmil - #4 AWG	2
1452129		2								
1453129		3								

CH = Available with hinge cover attached
See pages 54-57 for dimensional information