

Double Row Terminal Blocks

672 RZ Series

600 Volts



Specifications:

- Base, Thermoplastic, 125°C (U.L. RTI)
- Closed Back Design
- Screws, #8-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-24 Poles
- 9/16" Centers
- Wire Range With Wire Binding Screw #10-#14 AWG – 30 Amps
- Wire Range With Sems Pressure Screw #10-#22 AWG Stranded Copper Wire Only – 30 Amps
- The Suitability Of These Devices For Greater Currents Shall Be Determined In The End-Use Application
- UL Recognized File No. XCFR2.E47811
- CSA Certified File No. LR19766
- CE

Catalog #	# of poles	Dimensions	
		A	B
672 RZ 01	1	1.54	1.13
672 RZ 02	2	2.10	1.69
672 RZ 03	3	2.66	2.25
672 RZ 04	4	3.22	2.81
672 RZ 05	5	3.79	3.38
672 RZ 06	6	4.35	3.94
672 RZ 07	7	4.91	4.50
672 RZ 08	8	5.47	5.06
672 RZ 09	9	6.04	5.63
672 RZ 10	10	6.60	6.19
672 RZ 11	11	7.16	6.75
672 RZ 12	12	7.72	7.31

Catalog #	# of poles	Dimensions	
		A	B
672 RZ 13	13	8.29	7.88
672 RZ 14	14	8.85	8.44
672 RZ 15	15	9.41	9.00
672 RZ 16	16	9.97	9.56
672 RZ 17	17	10.54	10.13
672 RZ 18	18	11.10	10.69
672 RZ 19	19	11.66	11.25
672 RZ 20	20	12.22	11.81
672 RZ 21	21	12.79	12.38
672 RZ 22	22	13.35	12.94
672 RZ 23	23	13.91	13.50
672 RZ 24	24	14.47	14.06

Top Mounted Hardware is .250" Wide
MM = Dim X 25.4

Hardware Options: (Hardware options may affect ratings - consult factory)

KT55	=	Full Quick Connect (0° Flat)	See Page 96
KT56	=	Full Quick Connect (45° Bend)	See Page 96
KT57	=	Full Quick Connect (90° Bend)	See Page 96
ST	=	Full Solder	See Page 97
J 602	=	Line to Line Jumper	See Page 99
3/4 ST	=	Half Solder	See Page 97
KT61	=	Half Quick Connect (0° Flat)	See Page 96
KT62	=	Half Quick Connect (45° Bend)	See Page 96
KT63	=	Half Quick Connect (90° Bend)	See Page 96
3786	=	Sems Pressure Saddle Screw	See Page 99
3787	=	Sems Pressure Saddle Screw with External Tooth Lock Washer	
PSB	=	Phil-Slot Brass Screw	

