

# Double Row Terminal Blocks

## 300 Series Kulka® 672 GP Series

### 600 Volts



#### Specifications:

- Base, General Purpose Phenolic, 150°C
- Closed Back Design
- Screws, #8-32 Binder Head, Phil-Slot, Steel
- Terminals, Plated Brass
- 1-24 Poles
- 9/16" Centers
- Wire Range with Wire Binding Screw # 10 - #14 AWG - 30 Amps
- Wire Range with Sems Pressure Screw #10 - #22 AWG Stranded Copper Wire Only, 30 Amps
- Will Accommodate Lugs for Wire Sizes #10 - #16 AWG - 30 Amps
- The Suitability of These Devices for Greater Currents Shall Be Determined in the End-Use Application
- UL Recognized File No. XCFR2.E62806
- CSA Certified File No. LR19766
- CE

MSP Catalog #	Kulka® Catalog #	# of poles	Dimensions	
			A	B
301	672 GP 01	1	1.54	1.13
302	672 GP 02	2	2.10	1.69
303	672 GP 03	3	2.66	2.25
304	672 GP 04	4	3.22	2.81
305	672 GP 05	5	3.79	3.38
306	672 GP 06	6	4.35	3.94
307	672 GP 07	7	4.91	4.50
308	672 GP 08	8	5.47	5.06
309	672 GP 09	9	6.04	5.63
310	672 GP 10	10	6.60	6.19
311	672 GP 11	11	7.16	6.75
312	672 GP 12	12	7.72	7.31

MSP Catalog #	Kulka® Catalog #	# of poles	Dimensions	
			A	B
313	672 GP 13	13	8.29	7.88
314	672 GP 14	14	8.85	8.44
315	672 GP 15	15	9.41	9.00
316	672 GP 16	16	9.97	9.56
317	672 GP 17	17	10.54	10.13
318	672 GP 18	18	11.10	10.69
319	672 GP 19	19	11.66	11.25
320	672 GP 20	20	12.22	11.81
321	672 GP 21	21	12.79	12.38
322	672 GP 22	22	13.35	12.94
323	672 GP 23	23	13.91	13.50
324	672 GP 24	24	14.47	14.06

Top Mounted Hardware is .250" Wide

MM = Dim x 25.4

#### Hardware Options: (Hardware options may affect ratings - consult factory)

MSP	KULKA		
(F1)	KT55	= Full Quick Connect (0° Flat)	See Page 96
(F2)	KT56	= Full Quick Connect (45° Bend)	See Page 96
(F3)	KT57	= Full Quick Connect (90° Bend)	See Page 96
(S)	ST	= Full Solder	See Page 97
(LL 300)	J 602	= Line to Line Jumper	See Page 99
(HS)	3/4 ST	= Half Solder	See Page 97
(HF1)	KT61	= Half Quick Connect (0° Flat)	See Page 96
(HF2)	KT62	= Half Quick Connect (45° Bend)	See Page 96
(HF3)	KT63	= Half Quick Connect (90° Bend)	See Page 96
(SP)	3786	= Sems Pressure Saddle Screw	See Page 99
(SPSE)		= Sems Pressure Saddle Screw with External Tooth Lock Washer	
	LWW	= Feed Thru Wire Wrap (1.00)	
(L)	Y	= Feed Thru Solder (.437)	
	YSY	= Feed Thru Solder (.625)	
	PSB	= Phil-Slot Brass Screw	

