

[Home](#) | [Products](#) | [About Us](#) | [Heat Technology](#) | [What's New](#) | [Parts & Service](#) | [Contact Us](#)

MICROTORCH® MODEL MT-30

MASTER®
APPLIANCE

Quick Jump: Model MT-30

A low profile, table-top microtorch with stable base for industrial and laboratory applications

- Built-in self-igniting system with safety lock that ensures the switch is not turned on when not in use
- Wide, stable base is perfect for bench-top use
- Butane-powered, eliminates the need for external fuel tanks, costly piping or unsightly hoses
- Durable self-contained, refillable metal fuel tank
- 60 minutes continuous run time with a full charge
- Adjustable broad flame or pinpoint flame
- Flame temperature approximately 2500°F
- Safety lock prevents unintentional ignition, locks for storage
- Refill with Master Ultratane Butane for best performance
- Use for industrial, institutional, scientific and dental laboratory applications, including shrinking tubing and specialty connectors, heating and spot drying materials, heating wax, jewelry repair and more



ORDERING INFORMATION

MODEL NO.	DESCRIPTION
MT-30	Microtorch, Low-Profile Table-Top

SPECIFICATIONS

■ Dimensions: 5.1" H x 3" W x 3.5" D	■ Net Weight: 12 oz.
■ Approx. Run Time: One Hour	■ Shipping Weight: 1 lb.
■ Approx. Flame Temp.: 2500° F	■ Shipped Empty
■ Recommended Fuel: Master Ultratane® Butane	■ Fuel Tank: Metal, Built-in, Refillable



ULTRATANE® BUTANE

Use Master Ultratane Butane for best performance. The only approved butane recommended to fuel all Master butane powered products.

Users should independently evaluate the suitability of the product for their application.

WARNING

The Department of Transportation Hazardous Material Regulations forbid carriage of butane or other flammable gas products on passenger aircraft. Do not pack this item or any other flammable gas item in any checked or carry-on baggage.

[HOME](#) [BACK TO PRODUCT LISTING](#)