

Rubber Renue 408B



Rejuvenates and conditions rubber. Apply with a cloth, brush, or swab to bring belts, platens, rollers, and rubber parts back to life.

- Zero residue
- CARB Compliant
- Fast dry
- Removes oxidation film
- 100% Ozone safe

Available Sizes

Catalog Number	Sizes Available	Description
408B-100ML	125 mL (4.2 oz)	Liquid
408B-250ML	250 mL (8.4 oz)	Liquid
408B-1L	1 L (33 oz)	Liquid
408B-4L	4 L (1 gal)	Liquid



Material Safety Data Sheet

Section 1: Product Identification

MSDS Code: 408B - Liquid

Name: Rubber Renue

Related Part Numbers: 408B-250ML

Use: Rejuvenates and conditions rubber.

Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
1330-20-7	Xylene	58-64%	100 ppm	N/E	150 ppm
119-36-8	Methyl Salicylate	15-16.5%	N/E	N/E	N/E
67-64-1	Acetone	23-25%	500 ppm	N/E	750 ppm

Section 3: Hazards Identification

Eyes: Causes eye irritation.

Skin: May cause skin irritation.

Inhalation: May cause drowsiness. Causes respiratory tract irritation.

Ingestion: Harmful if swallowed. May cause nausea and vomiting.

Chronic: May cause liver and kidney damage. Repeated exposure may cause metabolic disturbances.

Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush with water or saline. Get medical aid.

Skin: Wash skin with soap and water. Get medical aid if symptoms persist.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Ingestion: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.

Section 5: Fire Fighting Measures

Autoignition Temperature: 454 **Flash Point:** 25°C **LEL / UEL:** 1/12

Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam.

General Information: Will burn if involved in a fire. Flash back along vapor trail is possible.

Section 6: Accidental Release Measures

Spill Procedure: Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection. Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further residue with paper towel and place in container. Wash spill area with soap and water.

Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do not expose container to heat or flame.

Storage: Keep away from sources of ignition. Store in a cool, dry, well-ventilated area, away from incompatible substances.

Section 8: Exposure Controls

Routes of entry: Eyes, ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

Personal Protection: Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

Section 9: Physical and Chemical Properties

Physical State:	Liquid	Odor:	Aromatic	Solubility in water:	Insoluble	Evaporation Rate:	Slow
Boiling Point:	72°C	Specific Gravity:	0.89	Vapor Pressure:	2 PSI @21°C	Vapor Density:	2 (Air=1) pH: 7

Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures.

Conditions to avoid: Temperatures over 40°C, ignition sources, and incompatible substances.

Incompatibilities: Strong oxidizers, acids, and bases.

Polymerization: Will not occur.

Decomposition: Carbon monoxide, carbon dioxide, salicylic acid.

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure) No

Carcinogenicity: (risk of cancer) No

Teratogenicity: (risk of malformation in an unborn fetus) The CCOHS list Xylene as a reproductive Hazard.

Reproductive Toxicity: (risk of sterility) No

Mutagenicity: (risk of heritable genetic effects) No

Lethal Exposure Concentrations:	Ingestion (LD50):	Inhalation (LC50):	Skin (LD50):	Inhalation (TCLo):
Xylene	2119 mg/kg Rat	5000 ppm/4H Rat	>1700 mg/kg Rabbit	1600 ppm/20H/7D (intermittent) Rat
Methyl Salicylate	887 mg/kg Rat	N/E	N/E	18 mg/m3 Rat
Acetone	3gm/kg Mouse	50,100 mg/m3/8H	>9400 uL/Kg Guinea Pig	30,000 mg/m3/2H Mouse

Section 12: Ecological Information

General Information:

Volatile Organic Compounds, % by weight: 75%

Volatile Organic Compounds, grams per litre: 667.5 g/l

Section 13: Disposal Information

General Information: Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff can cause environmental damage.

Section 14: Transportation Information

Ground Canada:

Classified as **Consumer Commodity**.

Recommend Shipper be trained and certified. Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations).

Ground USA:

Classified as **ORM-D**.

Recommend Shipper be trained and certified. Refer to USA CFR 49 Regulations (Parts 100 to 185).

Air: (all sizes).

Shipper must be trained and certified. Refer to IATA Dangerous Goods Regulations.

UN number: **1993**, Shipping Name: **Flammable liquid, n.o.s.**, Class: **3**, Packing Group: **II**, Flash Point: **25°C**.
Subsidiary Risk – nil, Recommend using original MG Chemicals certified outer cartons. Tape all seams on the carton.
Hazard Label required – Flammable Liquid. A double arrow orientation label is required and is already printed on the original outer carton.

Sea - All Sizes:

Shipper must be trained and certified. Refer to IMDG regulations.

UN number: **1993**, Shipping Name: **Flammable liquid, n.o.s.**, Class: **3**, Packing Group: **II**, Flash Point: **25°C**.
Storage category "A", segregation as for class 9 but away from sources of heat and separated from goods of class 1 except for those in division 1.4.

Section 15: Regulatory Information

CANADA

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

DSL

All ingredients in this product are listed on the Domestic Substances List

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling regulations.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

WHMIS

This product belongs to the following categories: **B2, D2A**

USA

CAA (Clean Air Act, USA)

This product does not contain any class 1-ozone depletors.

This product does not contain any class 2-ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

This product contains **Xylene (CAS# 1330-20-7, 60%)** a toxic chemical subject to the reporting requirements of section 313 of Title III of the superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains the following chemical subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372 (**Xylene (CAS# 1330-20-7, 60%)**)

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.