

Silver Conductive Coating



8420

Resistivity: 0.01 Ohm · mil

Reduces or eliminates EMI / RFI interference. A general purpose EMI / RFI shielding for use on plastic electronics enclosures. Consists of a tough, durable acrylic base pigmented with a high purity silver coated copper. Has a resistance of 0.01 ohms · cm.

Covers approximately 8300 square inches.

Available Sizes

Catalog Number	Sizes Available	Description
8420-900ML	(0.23 gal, 4 lbs)	Liquid



Technical Data Sheet

PRODUCT NAME

Super Shield Silver Conductive Coating

PRODUCT DESCRIPTION

Reduces or eliminates EMI / RFI interference. Consists of a tough, durable acrylic base pigmented with a high purity silver. Has a resistance of 0.01 ohm • cm.

PRODUCT FEATURES / BENEFITS

High conductivity

Durable acrylic base

Specifications

Resistivity	0.01 ohm • cm
Tack Free Time	10 minutes at 20°C (68°F)
Full Cure	24 hours at 20°C (68°F)
Silver content (solid %)	55
Operating Temperature	-30°C to 100 °C (-22 °F to 212 °F)

AVAILABILITY

8420-900ML 1.6 kg

Material Safety Data Sheet

Section 1: Product Identification

MSDS Code: 8420 - liquid Name: Super Shield Silver Conductive Coating

Related Part Numbers: 8420-900ML

Use: For reducing EMI / RFI interference.

Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
7440-22-4	Silver	50 - 60	1mg/m ³	1mg/m ³	N/e
78-93-3	2-butanone	3 - 5	200ppm	200ppm	300ppm
1330-20-7	Xylenes	3 - 5	100ppm	100ppm	150ppm
108-88-3	Toluene	3 - 5	50ppm	100ppm	150ppm
141-78-6	Ethyl acetate	2 - 3	400ppm	400ppm	N/e
108-65-6	1-methoxy-2-propanol acetate	1 - 2	N/e	N/e	N/e
71-36-3	n-butyl alcohol	1 - 2	50ppm	100ppm	N/e
763-69-9	Glycol ether ester	1 - 2	50ppm	N/e	N/e
67-56-1	Methyl alcohol	<1	200ppm	200ppm	250ppm
67-63-0	2-propanol	<1	400ppm	400ppm	500ppm

Section 3: Hazards Identification

WHMIS Codes: B2, D2A

NFPA Ratings: Health 1 Flammability 3 Reactivity 1

HMIS Ratings: Health 1 Flammability 3 Reactivity 1

Eyes: Causes severe eye irritation, tearing, redness, and blurred vision. Vapors from this product are irritating to the eye.

Skin: May cause skin irritation. May cause defatting of skin.

Inhalation: Product is irritating to the nose, throat, and respiratory tract. May cause liver and kidney damage, and central nervous system depression.

Ingestion: Harmful if swallowed. Ingestion of large amounts may cause nausea, gastrointestinal upset, and pain. May cause liver and kidney damage, and central nervous system depression.

Chronic: May cause liver and kidney damage.

Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush with water or saline for 20 minutes. Get medical aid.

Skin: Wash skin with large quantities of soap and water. Get medical aid if symptoms persist.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Ingestion: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.

Section 5: Fire Fighting Measures

Autoignition Temperature: 465°C **Flash Point:** -18°C **LEL / UEL:** 1 / 36

Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or chemical foam.

General Information: Will burn if involved in a fire. Flash back along vapor trail is possible.

Section 6: Accidental Release Measures

Spill Procedure: Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection. Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further residue with paper towel and place in container. Wash spill area with soap and water.

Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do not expose container to heat or flame.

Storage: Keep away from sources of ignition. Store in a cool, dry, well-ventilated area, away from incompatible substances. Keep from freezing.

Section 8: Exposure Controls

Routes of entry: Eyes, ingestion, inhalation, and skin.

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

Personal Protection: Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

Section 9: Physical and Chemical Properties

Physical State:	Liquid	Odor:	Ethereal	Solubility:	Partial	Evaporation Rate:	Fast		
Boiling Point:	59°C	Specific Gravity:	1.85	Vapor Pressure:	1PSI @21°C	Vapor Density:	4.1 (Air=1)	pH:	7

Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures.

Conditions to avoid: Temperatures over 40°C, ignition sources, and incompatible substances.

Incompatibilities: Alkali and alkaline earth metals, powdered aluminum, zinc, magnesium, and beryllium, lithium aluminum hydride, potassium tert-butoxide, nitrates, strong acids, strong oxidizers, chlorosulphonic acid, hydrogen peroxide.

Polymerization: Will not occur.

Decomposition: Carbon monoxide, carbon dioxide, nitrogen oxides

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure)	Prolonged or repeated skin contact may cause dermatitis.		
Carcinogenicity: (risk of cancer)	No		
Teratogenicity: (risk of malformation in an unborn fetus)	This product contains xylene, a known embryo toxin. Pregnant women must avoid all contact with this product.		
Reproductive Toxicity: (risk of sterility)	Toluene is listed under California Proposition 65 under chemicals known to cause reproductive toxicity.		
Mutagenicity: (risk of heritable genetic effects)	No		
Lethal Exposure Concentrations:	Ingestion (LD50): 7400 mg/kg (rat)	Inhalation (LC50): 16000 ppm/4h (rat)	Skin (LD50): N/e

Section 12: Ecological Information

General Information: Avoid runoff into storms and sewers, which lead into waterways. Water runoff can cause environmental damage.

Environmental Impact Data: (percentage by weight)

CFC: 0 **HFC:** **Cl.Solv:** 0 **VOC:** 53 **HCFC:** 0 **ODP:** 0

Section 13: Disposal Information

General Information: Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff can cause environmental damage.

Section 14: Transportation Information

Ground:

Consumer Commodity, ORM-D

Air:

Shipper must be trained and certified. Refer to IATA regulations.

Sea:

Shipper must be trained and certified. Refer to IMDG regulations.

Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

This product contains the following chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372: Methanol (CAS #67-56-1, 2% by weight), Silver (CAS # 7440-22-4, 50-60%), Xylenes (CAS # 1330-20-7, 3-5%), Toluene CAS #108-88-3, 3-5%), n-Butyl alcohol CAS #71-36-3, 1-2%) Methyl alcohol CAS# 67-56-1 <1%) 2-Butanone CAS # 78-93-3, 3-5%)

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains the following chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372: Methanol (CAS #67-56-1, 2% by weight), Silver (CAS # 7440-22-4, 50-60%), Xylenes (CAS # 1330-20-7, 3-5%), Toluene CAS #108-88-3, 3-5%), n-Butyl alcohol CAS #71-36-3, 1-2%) Methyl alcohol CAS# 67-56-1 <1%) 2-Butanone CAS # 78-93-3, 3-5%)

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.