

RTV Silicones by MOMENTIVE performance materials 1-Part Adhesive Sealant RTV6708



Primary Characteristics Translucent paste High Strength Modified alkoxy

- neutral cure
- ▶ UL HB Recognition
- ▶ UL File No. <u>E36952</u>

The RTV6708 is an economical alternative useful in many applications where an adhesive sealant is required.

Available Sizes

Catalog Number	Sizes Available	Description
RTV6708-300ML	300 mL (10 oz)	cartridge

Specifications

Use	Adhesive Sealant		
Special Feature	General use		
Standards	UL HB recognition		
Cross Reference	n/a		
Uncured Properties			
Consistency	Paste		
Color	translucent		
Specific Gravity	1.04		
Tack Free Time	25 min		
Cure Through Time (77°F / 50% relative humidity / 1/8" thick)	24 hours		
Useful Temp. Range	-60°C to 205°C (-75°F to 400°F)		
Cured Properties - MECHANICAL			
<u>Hardness</u>	18 (Shore A)		
Tensile Strength	1.57 MPa (225 psi)		
Elongation	450%		
Cured Properties - ELECTRICAL			
Dielectric Strength	16 kV/mm (410 V/mil)		
Dielectric Constant	2.9 @ 60 Hz		
Other			
Viscosity (@ 25°C)	175 g/min		