

Micro Commercial Components Corp.

Complete Discrete Semiconductor Solutions

| N5402 FANDARD RECOVERY RECTIFIERS D-201AD DOV |
|---|
| O-201AD 00V |
| 00V |
| |
| 20.4 |
| A00 |
| OA |
| ov |
| OA |
| |
| ΟμΑ |
| 00V |
| ulk: 500pcs/Box, 12K/Ctn; Tape: 1.2K/Reel, 4.8K/Ctn; T/B: 2K/Ammo Box, 12K/Ctn. |
| |

This product is listed under the following categories where you may find similar products: Diodes

Standard Recovery Rectifiers



1N5400 THRU 1N5408

Features

- Low Current Leakage and Low Forward Voltage
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 30°C/W Junction To Lead

| MCC | Device | Maximum | Maximum | Maximum |
|---------|---------|-----------|---------|----------|
| Catalog | Marking | Recurrent | RMS | DC |
| Number | | Peak | Voltage | Blocking |
| | | Reverse | | Voltage |
| | | Voltage | | |
| 1N5400 | 1N5400 | 50V | 35V | 50V |
| 1N5401 | 1N5401 | 100V | 70V | 100V |
| 1N5402 | 1N5402 | 200V | 140V | 200V |
| 1N5404 | 1N5404 | 400V | 280V | 400V |
| 1N5405 | 1N5405 | 500V | 350V | 500V |
| 1N5406 | 1N5406 | 600V | 420V | 600V |
| 1N5407 | 1N5407 | 800V | 560V | 800V |
| 1N5408 | 1N5408 | 1000V | 700V | 1000V |


Electrical Characteristics @ 25°C Unless Otherwise Specified

| iceti icai oriai acteri istica e 20 o oriicas otrici wiac apecinic | | | | |
|--|--------------------|----------------|---|--|
| Average Forward Current | I _{F(AV)} | 3.0A | T _a = 105°C | |
| Peak Forward Surge Current | I _{FSM} | 200A | 8.3ms, half sine | |
| Forward Voltage | V_{F} | 1.0V | I _F = 3.0A; T _a = 25°C | |
| Maximum DC Reverse Current At Rated DC Blocking Voltage | I _R | 5.0μA 100μA | T _a = 25°C T _a = 150°C | |
| Typical Junction Capacitance | C _J | 40pF | Measured at 1.0MHz, V _R =4.0V | |

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.

3 Amp Rectifier 50 - 1000 Volts

DO-201AD



| DIMENSIONS | | | | | |
|------------|--------|------|---------|------|------|
| | | | | | |
| | INCHES | | CHES MM | | |
| DIM | MIN | MAX | MIN | MAX | NOTE |
| Α | .287 | .374 | 7.30 | 9.50 | |
| В | .189 | .208 | 4.80 | 5.30 | |
| С | .048 | .052 | 1.20 | 1.30 | |
| D | 1.000 | | 25.40 | | |



Ordering Information

| Device | Packing |
|------------------|------------------------------|
| (Part Number)-TP | Tape&Reel 1.2Kpcs/Reel |
| (Part Number)-AP | Ammo Packing;1.2Kpcs/AmmoBox |
| (Part Number)-BP | Bulk;500pcs/Box |

IMPORTANT NOTICE

Micro Commercial Components Corp. reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.