

| 0669 | 0670 | 0673 | 0666 |
|---|---|---|---|
| | | | |
| <p>0669-0-15-XX-30-XX-10-0 Solder mount in .060 min. mounting hole</p> | <p>0670-0-15-XX-30-XX-10-0 Solder mount in .060 min. mounting hole</p> | <p>0673-0-15-XX-30-XX-10-0 Surface Mount</p> | <p>0666-0-15-XX-32-XX-10-0 Solder mount in .064 min. mounting hole Also available on 24mm wide carrier tape: 1,500 parts per 13" reel. Order as: 0666-0-57-XX-32-XX-10-0</p> |

| 0341 | 0252 | 0678 | 0676 |
|--|--|---|---|
| | | | |
| <p>0341-0-15-XX-30-XX-10-0 Solder mount in .073 mounting hole</p> | <p>0252-0-15-XX-32-XX-10-0 Hex press-fit in .057 plated thru hole</p> | <p>0678-0-15-XX-32-XX-10-0 Press-fit in .057 mounting hole</p> | <p>0676-0-15-XX-30-XX-10-0 Press-fit in .057 mounting hole</p> |

| 0697 | 0668 | 0253/1033 |
|---|---|---|
| | | |
| <p>0697-0-15-XX-30-XX-10-0 Press-fit in .057 mounting hole</p> | <p>0668-0-15-XX-30-XX-10-0 Press-fit in .057 mounting hole</p> | <p>XXX3-0-15-XX-30-XX-10-0 Press-fit in .057 mounting hole</p> |

| Basic Part Number | Length L | Depth N |
|-------------------|----------|---------|
| 0253-0 | .173 | .148 |
| 1033-0 | .203 | .162 |

| | | |
|--|--|---|
| <p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p> | <p>ORDER CODE: XXXX - X - 15 - XX - 3X - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <p>01 200µ" TIN/LEAD OVER NICKEL</p> <p>80 200µ" TIN OVER NICKEL ◊</p> <p>15 10µ" GOLD OVER NICKEL ◊</p> <p>SELECT CONTACT</p> <p>#30 or #32 CONTACT (DATA ON PAGES 218 & 219)</p> | <p>SPECIFY CONTACT FINISH:</p> <p>02 100µ" TIN/LEAD OVER NICKEL</p> <p>84 100µ" TIN OVER NICKEL ◊</p> <p>27 30µ" GOLD OVER NICKEL ◊</p> |
|--|--|---|

