

<p>0394</p> <p>0394-0-15-XX-07-XX-10-0 Solder mount in .120 min. mounting hole</p>	<p>0393</p> <p>0393-0-15-XX-07-XX-10-0 Solder mount in .144 min. mounting hole</p>	<p>0391</p> <p>0391-0-15-XX-07-XX-10-0 Solder mount in .159 min. mounting hole</p>	<p>9016</p> <p>9016-0-15-XX-07-XX-10-0 Press-fit in .131 mounting hole</p>
--	--	--	--

<p>0493</p> <p>0493-0-15-XX-07-XX-10-0 Press-fit in .144 mounting hole</p>	<p>0490</p> <p>0490-0-15-XX-07-XX-04-0 Press-fit in .144 mounting hole</p>	<p>0616</p> <p>0616-0-18-XX-07-XX-10-0 Press-fit in .144 mounting hole</p>	<p>0387</p> <p>0387-0-15-XX-07-XX-04-0 Solder mount in .063 min. mounting hole</p>
--	--	--	--

<p>0370</p> <p>0370-0-19-XX-07-XX-10-0 #18 Gage crimp barrel</p>	<p>4040</p> <p>4040-0-19-XX-07-XX-10-0 Wire Termination</p>	<p>0491</p> <p>0491-0-19-XX-07-XX-04-0 For use in stackable patch cords</p>	<p>9214</p> <p>9214-0-15-XX-07-XX-10-0 Solder mount in .083 min. mounting hole</p>
--	---	---	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - 07 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <p>01 200μ" TIN/LEAD OVER NICKEL</p> <p>80 200μ" TIN OVER NICKEL ◊</p> <p>15 10μ" GOLD OVER NICKEL ◊</p> <p>CONTACT →</p> <p>#07 CONTACT (DATA ON PAGE 225)</p>	<p>SPECIFY CONTACT FINISH:</p> <p>01 200μ" TIN/LEAD OVER NICKEL</p> <p>80 200μ" TIN OVER NICKEL ◊</p> <p>27 30μ" GOLD OVER NICKEL ◊</p>
--	---	---

