



0980




0980-0-15-20-75-14-11-0
Double action, *.055 Combined Stroke
Mount between parallel circuit boards

0925




0925-0-15-20-73-14-26-0
Standard Stroke
Surface Mount

0930




0930-0-15-20-75-14-11-0
Standard Stroke
Solder Mount in .018 min. mounting hole

0932




0932-0-15-20-77-14-11-0
Long Stroke
Solder Mount in .027 min. mounting hole

0934




0934-0-15-20-74-14-26-0
Standard Stroke
Surface Mount

0927




0927-0-15-20-75-14-11-0
Standard Stroke
Surface Mount

0928




0928-0-15-20-77-14-11-0
Long Stroke
Surface Mount

0929




0929-0-15-20-75-14-11-0
Standard Stroke
Solder Mount in .027 min. mounting Hole

0936



0936-0-15-20-75-14-11-0
Standard Stroke
Surface Mount


0908-X



0908-X-15-20-75-14-11-0
Standard Stroke
Solder mount in .018 min. mounting hole

| Basic Part Number | Length A |
|-------------------|----------|
| 0908-0 | .255 |
| 0908-1 | .275 |
| 0908-2 | .295 |
| 0908-3 | .315 |
| 0908-4 | .335 |
| 0908-5 | .350 |
| 0908-6 | .370 |
| 0908-7 | .390 |
| 0908-8 | .410 |
| 0908-9 | .430 |

0950



0950-0-15-20-71-14-11-0
Standard Stroke
Solder Mount in .018 min. mounting hole

ORDER CODE: 09XX - X - 15 - 20 - 7X - 14 - 11 - 0
Spring Number

MATERIAL SPECIFICATIONS:
SLEEVE & PLUNGER MATERIAL: Copper Alloy
SPRING MATERIAL: Beryllium Copper
SLEEVE & PLUNGER FINISH: 20 μ" Gold over Nickel
SPRING FINISH: 10 μ" Gold over Nickel
DIMENSION IN INCHES:
TOLERANCES ON: LENGTHS: ±.006
DIAMETERS: ±.002
ANGLES: ± 2°



MECHANICAL & ELECTRICAL SPECIFICATIONS:
DURABILITY: 1,000,000 cycles
CURRENT RATING: 2A continuous, 3A peak
CONTACT RESISTANCE: 20 mΩ max.

| SPRING NUMBER | Mid. STROKE | Max. STROKE | FORCE @ Mid. Stroke | Initial Force (Pre-load) |
|---------------|-------------|-------------|---------------------|--------------------------|
| 71 | .0275 | .055 | 50 | 15 |
| 73 | .0275 | .055 | 60 | 25 |
| 74 | .0275 | .055 | 50 | 15 |
| 75 | .0275 | .055 | 60 | 25 |
| 77 | .045 | .090 | 60 | 25 |

71, 73, 74, 75, 77 Springs are not Interchangeable