

- Low profile DIP socket, sits only .122" above the PCB.
- Hi-Rel, 4-finger BeCu #30 contact is rated at 3 amps. See page 218 for details.
- Series 115 use MM #0501 pins. See page 133 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	<h2 style="margin: 0;">Ordering Information</h2>	
	A	B	C			

10	0.5	0.2	0.3	41	115-XX-210-41-001000	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> <b>RoHS</b> 2002/95/EC         </div> <div style="border: 1px solid green; padding: 2px; margin-top: 5px; font-size: small;">           For RoHS compliance select <span style="color: green;">◇</span> plating code.         </div>
4	0.2	0.3	0.4	102	115-XX-304-41-001000	
6	0.3	0.3	0.4	67	115-XX-306-41-001000	
8	0.4	0.3	0.4	50	115-XX-308-41-001000	
10	0.5	0.3	0.4	40	115-XX-310-41-001000	
14	0.7	0.3	0.4	28	115-XX-314-41-001000	
16	0.8	0.3	0.4	25	115-XX-316-41-001000	
18	0.9	0.3	0.4	22	115-XX-318-41-001000	
20	1.0	0.3	0.4	20	115-XX-320-41-001000	
22	1.1	0.3	0.4	18	115-XX-322-41-001000	
24	1.2	0.3	0.4	16	115-XX-324-41-001000	
28	1.4	0.3	0.4	14	115-XX-328-41-001000	
20	1.0	0.4	0.5	20	115-XX-420-41-001000	
22	1.1	0.4	0.5	18	115-XX-422-41-001000	
24	1.2	0.4	0.5	16	115-XX-424-41-001000	
28	1.4	0.4	0.5	14	115-XX-428-41-001000	
32	1.6	0.4	0.5	12	115-XX-432-41-001000	
24	1.2	0.6	0.7	16	115-XX-624-41-001000	
28	1.4	0.6	0.7	14	115-XX-628-41-001000	
32	1.6	0.6	0.7	12	115-XX-632-41-001000	
36	1.8	0.6	0.7	11	115-XX-636-41-001000	
40	2.0	0.6	0.7	10	115-XX-640-41-001000	
42	2.1	0.6	0.7	9	115-XX-642-41-001000	
48	2.4	0.6	0.7	8	115-XX-648-41-001000	
50	2.5	0.6	0.7	8	115-XX-650-41-001000	
52	2.6	0.6	0.7	7	115-XX-652-41-001000	
50	2.5	0.9	1.0	8	115-XX-950-41-001000	<div style="border: 1px solid black; border-radius: 50%; padding: 10px; display: inline-block;"> <b>XX=Plating Code</b> See Below         </div>
52	2.6	0.9	1.0	7	115-XX-952-41-001000	
64	3.2	0.9	1.0	6	115-XX-964-41-001000	

For Electrical, Mechanical & Environmental Data, See pg. 4

**XX=Plating Code**  
See Below

SPECIFY PLATING CODE XX=			<b>93</b>			<b>43◇</b>	
Sleeve (Pin)			200μ" Sn/Pb			200μ" Sn	
Contact (Clip)			30μ" Au			30μ" Au	