



# PRODUCT SPECIFICATION

## .093 SERIES HIGH CURRENT END-CARRIED TERMINALS

### 1.0 SCOPE

This Product Specification covers the .093 Series 6.71 mm (.264 inch) centerline (pitch) 3191 Series and the 5.03 mm (.198 inch) centerline Standard .093 Series connectors using.

### 2.0 PRODUCT DESCRIPTION

#### 2.1 PRODUCT SERIES NUMBER AND DESCRIPTION

42477 / 42478 - .093 SERIES HIGH CURRENT, END-CARRIED CRIMP TERMINALS

3191 - .093 SERIES TYPE PLUG AND RECEPTACLE HOUSINGS

1261,1292, 1360.1375, 1396, 1490, 1545, 1619, 1951, 2163, 2629 - STANDARD .093 SERIES PLUG AND RECEPTACLE HOUSINGS

#### 2.2 DIMENSIONS, MATERIALS, PLATINGS AND MARKINGS

See the appropriate sales drawings of above series numbers for further information on dimensions, materials, platings and markings.

#### 2.3 SAFETY AGENCY APPROVALS

UL File #E29179  
CSA File #LR19980  
TUV License #R75107

### 3.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS

MIL-STD-1344A  
UL 1682

### 4.0 RATINGS

#### 4.1 VOLTAGE

600 Volts AC (RMS) for 3191 Series  
250 Volts AC (RMS) for Standard .093 Series

#### 4.2 CURRENT AND APPLICABLE WIRES

AWG	Amps	Outside Insulation Diameter
14	17	3.56 mm (.140 inch)
18	12	2.79 mm (.110 inch)

#### 4.3 TEMPERATURE

Operating: - 55°C to + 105°C

<u>REVISION:</u> <b>B</b>	<u>ECR/ECN INFORMATION:</u> EC No: <b>UCR2002-0301</b> DATE: <b>09 / 26 / 01</b>	<u>TITLE:</u> <b>PRODUCT SPECIFICATION .093 DIA. HIGH CURRENT TERMINALS IN 3191 &amp; STD. .093 SERIES HSGS.</b>	<u>SHEET No.</u> <b>1 of 4</b>
<u>DOCUMENT NUMBER:</u> <b>PS-42477</b>	<u>CREATED / REVISED BY:</u> <b>BWIRKUS 9/26/01</b>	<u>CHECKED BY:</u> <b>BWIRKUS 9/26/01</b>	<u>APPROVED BY:</u> <b>SFRY 10/5/01</b>



# PRODUCT SPECIFICATION

## 5.0 PERFORMANCE

### 5.1 ELECTRICAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
1	Contact Resistance (Low Level)	Mate connectors: apply a maximum voltage of 20 mV and a current of 20 mA. (Measurement locations in Section 7.0)	10 milliohms MAXIMUM [initial]
2	Contact Resistance of Wire Termination (Low Level)	Terminate the applicable wire to the terminal and measure wire using a voltage of 20 mV and a current of 100 mA. (Measurement locations in Section 7.0)	2 milliohms MAXIMUM [initial]
3	Dielectric Withstanding Voltage	Mate connectors: apply a voltage of 5000 VAC for the 3191 Series, 2000 VAC for the .093 Series for 1 minute between adjacent terminals and between terminals to ground.	No breakdown; current leakage < 5 mA
4	Temperature Rise (via Current Cycling)	Mate connectors: measure the temperature rise at the rated current, subjecting the connector to : 96 hours of continuous current, followed by 240 hours of current cycling (45 minutes ON and 15 minutes OFF per hour).	Temperature rise: +30°C MAXIMUM

### 5.2 MECHANICAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
5	Terminal Insertion Force	Insert terminal into housing until fully locked at a rate of 25 ± 6 mm (1 ± ¼ inch) per minute.	22.2 N (5 lbf) MAXIMUM insertion force
6	Connector Mate and Unmate Forces	Mate and unmate connector (male to female) at a rate of 25 ± 6 mm (1 ± ¼ inch) per minute.	15.6 N (3.5 lbf) MAXIMUM insertion force 6.7 N (1.5 lbf) MINIMUM [initial] withdrawal force
7	Terminal Retention Force (in Housing)	Axial pullout force on the terminal in the housing at a rate of 25 ± 6 mm (1 ± ¼ inch) per minute.	89.0 N (20 lbf) MINIMUM retention force
8	Durability	Mate connectors up to {25 cycles for tin (non-noble) plating OR 250 cycles for gold (noble) plating} at a maximum rate of 5 cycles per minute prior to Environmental Tests.	10 milliohms MAXIMUM (change from initial)
9	Vibration (Random)	Subject mated connectors to vibration with an amplitude of 1.52 mm (.060 inch) peak to peak; a sweep of 10-55-10 hertz in 1.0 min.; and a duration of 2.0 hours in the ±X,±Y,±Z axes.	10 milliohms MAXIMUM (change from initial) & Discontinuity < 1 microsecond

REVISION: <b>B</b>	ECR/ECN INFORMATION: EC No: UCR2002-0301 DATE: 09 / 26 / 01	TITLE: <b>PRODUCT SPECIFICATION .093 DIA. HIGH CURRENT TERMINALS IN 3191 &amp; STD. .093 SERIES HSGS.</b>	SHEET No. <b>2 of 4</b>
DOCUMENT NUMBER: <b>PS-42477</b>	CREATED / REVISED BY: <b>BWIRKUS 9/26/01</b>	CHECKED BY: <b>BWIRKUS 9/26/01</b>	APPROVED BY: <b>SFRY 10/5/01</b>



# PRODUCT SPECIFICATION

## 5.2 MECHANICAL REQUIREMENTS (CONTINUED)

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
10	<b>Shock (Mechanical)</b>	Subject mated connectors to 3 shocks at <b>50 g's</b> with ½ sine wave (11 milliseconds) shocks in the ±X,±Y,±Z axes ( <b>18 shocks</b> total).	<b>10 milliohms MAXIMUM</b> (change from initial) & Discontinuity < <b>1 microsecond</b>
11	<b>Wire Pullout Force (Axial)</b>	Apply an axial pullout force on the wire at a rate of <b>25 ± 6 mm (1 ± ¼ inch)</b> .	<b>*** N (***) lbf)</b> MINIMUM pullout force {Recommended minimum value: 75% of tensile strength of the wire}
12	<b>Wire Pullout Force (Right Angle)</b>	Apply a right angle pullout force on the wire at a rate of <b>25 ± 6 mm (1 ± ¼ inch)</b> .	MINIMUM pullout force: <b>18 AWG: 89 N (20 lbf)</b> <b>16 AWG: 133 N (30 lbf)</b> <b>14 AWG: 267 N (60 lbf)</b> {Recommended minimum value: 75% of tensile strength of the wire}
13	<b>Terminal Insertion Force (into Housing)</b>	Apply an axial insertion force on the terminal at a rate of <b>25 ± 6 mm (1 ± ¼ inch)</b> .	<b>22 N (5 lbf)</b> MAXIMUM insertion force

## 5.3 ENVIRONMENTAL REQUIREMENTS

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT										
14	<b>Shock (Thermal)</b>	Mate connectors; expose to <b>10</b> cycles of: <table border="1"> <thead> <tr> <th>Temperature °C</th> <th>Duration (Minutes)</th> </tr> </thead> <tbody> <tr> <td>-40 +0/-3</td> <td>30</td> </tr> <tr> <td>+25 ±10</td> <td>5 MAXIMUM</td> </tr> <tr> <td>+105 +3/-0</td> <td>30</td> </tr> <tr> <td>+25 ±10</td> <td>5 MAXIMUM</td> </tr> </tbody> </table>	Temperature °C	Duration (Minutes)	-40 +0/-3	30	+25 ±10	5 MAXIMUM	+105 +3/-0	30	+25 ±10	5 MAXIMUM	<b>10 milliohms MAXIMUM</b> (change from initial) & Visual: No Damage
Temperature °C	Duration (Minutes)												
-40 +0/-3	30												
+25 ±10	5 MAXIMUM												
+105 +3/-0	30												
+25 ±10	5 MAXIMUM												
15	<b>Humidity (Cyclic)</b>	Expose mated connectors to a temperature cycles of <b>25 ± 3°C</b> at <b>95 ± 5%</b> relative humidity and <b>65 ± 3°C</b> at <b>50 ± 5%</b> relative humidity; dwell time of <b>1.0</b> hour; ramp time of <b>0.5</b> hours for <b>240</b> hours.	<b>10 milliohms MAXIMUM</b> (change from initial) & Dielectric Withstanding Voltage: No Breakdown at <b>500 VAC</b> & Insulation Resistance: <b>1000 Megohms MINIMUM</b> & Visual: No Damage										
16	<b>Salt Spray</b>	Mate connectors: Duration: <b>96</b> hours exposure; Atmosphere: salt spray from a <b>5%</b> solution; Temperature: <b>35 +1/-2°C</b>	<b>10 milliohms MAXIMUM</b> (change from initial) & Visual: No Damage										

REVISION: <b>B</b>	ECR/ECN INFORMATION: EC No: <b>UCR2002-0301</b> DATE: <b>09 / 26 / 01</b>	TITLE: <b>PRODUCT SPECIFICATION .093 DIA. HIGH CURRENT TERMINALS IN 3191 &amp; STD. .093 SERIES HSGS.</b>	SHEET No. <b>3 of 4</b>
DOCUMENT NUMBER: <b>PS-42477</b>	CREATED / REVISED BY: <b>BWIRKUS 9/26/01</b>	CHECKED BY: <b>BWIRKUS 9/26/01</b>	APPROVED BY: <b>SFRY 10/5/01</b>



# PRODUCT SPECIFICATION

## 5.3 ENVIRONMENTAL REQUIREMENTS (continued)

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
17	Thermal Aging	Mate connectors; expose to: <b>240</b> hours at <b>105 ± 2°C</b>	<b>10</b> milliohms MAXIMUM (change from initial]) & Visual: No Damage
18	Humidity (Steady State)	Mate connectors: expose to a temperature of <b>40 ± 2°C</b> with a relative humidity of <b>90-95%</b> for <b>240</b> hours.	<b>10</b> milliohms MAXIMUM (change from initial) & Dielectric Withstanding Voltage: No Breakdown at <b>500 VAC</b> & Insulation Resistance: <b>1000</b> Megohms MINIMUM & Visual: No Damage

## 6.0 PACKAGING

Parts shall be packaged to protect against damage during handling, transit and storage.

REVISION: <b>B</b>	ECR/ECN INFORMATION: EC No: <b>UCR2002-0301</b> DATE: <b>09 / 26 / 01</b>	TITLE: <b>PRODUCT SPECIFICATION .093 DIA. HIGH CURRENT TERMINALS IN 3191 &amp; STD. .093 SERIES HSGS.</b>	SHEET No. <b>4 of 4</b>
DOCUMENT NUMBER: <b>PS-42477</b>	CREATED / REVISED BY: <b>BWIRKUS 9/26/01</b>	CHECKED BY: <b>BWIRKUS 9/26/01</b>	APPROVED BY: <b>SFRY 10/5/01</b>