









Compare Products
Cable Assemblies [Overview](#)

[[Home](#) > [Products](#) > [Cable Assemblies](#) > [Compare Products](#)]

3 Matching Products

	 44995-0010	 44995-0020	 44995-0045
	Cable Assembly, IEEE 1394b-2002 Bilingual-to-IEEE 1394-1995, 1.0m	Cable Assembly, IEEE 1394b-2002 Bilingual-to-IEEE 1394-1995, 2.0m	Cable Assembly, IEEE 1394b-2002 Bilingual-to-IEEE 1394-1995, 4.5m
Cable Length	1.0m (3.28 ft)	2.0m (6.56 ft)	4.5m (14.8 ft)
	Common Features		
Status	INACTIVE / OBSOLETE		
Access Level	Internet		
Obsolete Date	2005-09		
Replacement Products	None		
Product Name	IEEE 1394		
Single Ended	No		
Connector to Connector	IEEE 1394b-2002 to IEEE 1394-1995		
Gender	Male - Male		
Circuits / Positions	9		
Shielded	Yes		
Pitch / Center Spacing	0.65mm (.026")		
Offset	No		
Contact	Copper (Cu) Alloy		
Plating Contact	Gold (Au)		

Under Plating	Nickel (Ni)		
Plating Other	Solder Tails and Shell: Tin/Lead (Sn/Pb)		
Wire Size [AWG]	24/30		
Wire Insulation Diameter	1.10mm (.043") max.		
Cable Type	Jacketed, PVC, Round		
Color	Gray		
Current-max [amps]	1.5A		
Voltage-max [volts]	30V		
Impedance	110 ohms		
Waterproof / Dustproof	IP54, IP65, IP67, NEMA 6P		
Product Specification	PS-45240-001		
Designed In	Millimeters		
Packaging	Bag		
Lock to Mating Part	Detent		
Mates With	44647, 45241		
Molex Series	44995		
Last Changed Date	2005-06		
Product Management	Guerrero, Jairo		
Lab Office	MEX		
	Cable Assembly, IEEE 1394b-2002 Bilingual-to-IEEE 1394-1995, 1.0m	Cable Assembly, IEEE 1394b-2002 Bilingual-to-IEEE 1394-1995, 2.0m	Cable Assembly, IEEE 1394b-2002 Bilingual-to-IEEE 1394-1995, 4.5m
	 44995-0010	 44995-0020	 44995-0045