



## 1/4" Prof. Phone Plugs, X-Series

Audio

[back](#)[Print](#)

### NP3X-B



The heavy duty professional phone plug series improves on the design of the existing C series by offering the thinnest available A-gauge 1/4" plug with unique Neutrik chuck type strain relief on the market. The slimline shell with a width of 14.5 mm meets the most recent requirements for highest density jackfields (15.88mm jack pitch). The precise machined one-piece tip contact without rivets makes it unique and avoids hook up in a socket or break off the tip. The Plug X Series serves all applications such as guitar applications, audio cables, snakes, speakers, amplifiers and mixing desks.

3 pole 1/4" professional phone plug, gold contacts, black shell

#### Features & Benefits

- Extra slim 1/4" plug for highest packing density
- Robust diecast shell in stylish design
- Improved chuck type strain relief for reliable cable retention
- Sleek design for best handling convenience
- Precision machined one-piece contacts - avoid hook up of tip contact

#### ACCESSORIES

BPX-\*




HTXP



PXR-\*





Allgemeintoleranzen ISO 2768-m	Werkstoff	Massstab:		Datum	Name
Zeichnung urheberrechtlich geschuetzt (DIN 34) (C)	-	2:1	Gezeichnet	26.01.04	Mijatovic
	-	(A4)	Freigegeben	-	-
Benennung	NP3X NP3X		Geändert	-	-
			Aend.-Nr.	-	Aend.-Index -
			Ersatz fuer:	Blatt 1 von 1 Bl.	
NEUTRIK AG FL-9494 SCHAAN			Zeichn. Nr.	ST-NP3X	




# NEUTRIK



## 1/4" Prof. Phone Plugs, X-Series

### NP3X-B



There are no technical infos for this product.

Product	
Connector Type	Plug
Gender	male
Electrical	
Contact resistance	depends on mating connector $\text{m}\Omega$
Dielectric strength	1 kVdc
Insulation resistance	$> 2 \text{ G}\Omega$ (initial)
Insulation resistance	$\geq 1 \text{ G}\Omega$ (after damp heat test)
Rated current per contact	$\leq 15 \text{ A}$
Mechanical	
Cable O.D.	4 - 7 mm
Wire size	1 $\text{mm}^2$
Wire size	18 AWG
Wiring	Solder contacts
Material	
Bushing	Polyacetal (POM) + PU
Contact plating	0.2 $\mu\text{m}$ Au
Contacts	Brass (CuZn39Pb3)
Insert	Polyamide (PA 6.6 30 % GR)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium
Strain relief	Polyacetal (POM)
Environmental	
Standard compliance	IEC 60603-11 / EIA RS-453

Solderability Complies with IEC 68-2-20

Temperature range -20 °C to +65 °C

**Optical**

**Mobile Cables**