


1757820-4 Product Details



1757820-4



[Active](#)

Subminiature D Pin/Socket Connectors for MIL-C-24308 and MIL-C-39029



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Connector
- Product Series = 109
- Density = Standard
- Terminate To Wire
- Number of Positions = 37

[View all Features](#) | [Find Similar Products](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [AMPLIMITE RECEPTACLE ASSY,SIZE 1 THRU 5 SERIES 109 W...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: [CAD Format & Compression Information](#)

- [2D Drawing](#) (DXF, Version B)
- [3D Model](#) (IGES, Version B)
- [3D Model](#) (STEP, Version B)

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Insert Arrangement](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Product Series](#) = 109
- [Number of Positions](#) = 37
- [Gender](#) = Receptacle
- [Shell Size](#) = 4
- [Shell Material](#) = Steel
- [Wire Termination Type](#) = Crimp
- Mounting Hole Diameter (mm [in]) = 3.05 [.120]

Body Related Features:

- [Blindmate](#) = No
- [Non-Magnetic](#) = No
- [Sockets](#) = Without
- [Rear Grommet](#) = No
- [Power/Signal/Coax Combination](#) = No
- [Shell Plating](#) = Zinc
- Mount Style = Mounting Holes
- Retention Clip Material = Stainless Steel

Contact Related Features:

- [Contact Size](#) = 20
- [Contact Style](#) = Crimp Snap-in

Configuration Related Features:

- [Density](#) = Standard

Industry Standards:

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M24308/2-284
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- NASA Qualification = No

Conditions for Usage:

- Terminate To = Wire

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Contact Customer Support](#)

[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2007 Tyco Electronics Corporation All Rights Reserved