

SNAP-LCE Controller

Features

- Runs up to 16 ioControl flowcharts simultaneously
- Works with all Opto 22 SNAP Ethernet-based I/O units
- Two serial ports for direct connection to serial devices
- Communicates on standard Ethernet networks or over a modem using PPP
- Includes FTP server/client capability and file system

Description

The SNAP-LCE Ethernet-based, stand-alone industrial controller is designed for use with Opto 22's ioControl™ Basic software, part of the ioProject™ Basic software suite. **Please note that SNAP-LCEs and ioProject are not recommended for new development.**

The last released version of ioProject Basic is version 7.1. This software will remain available on our website for some time to support customers who have existing SNAP-LCE controllers. **For new development, we recommend SNAP-PAC controllers (either standalone or on-the-rack) and PAC Project software.** See form #1688, the *SNAP PAC System Migration Technical Note*, for guidelines on mixing older and newer hardware and software.

The SNAP-LCE provides real-time control and communication to SNAP Ethernet-based input/output (I/O) systems and computer networks. Independently running a control program you build with the included ioControl development software, the SNAP-LCE monitors and controls all kinds of devices and equipment. It also communicates data about these devices and equipment directly to Opto 22's ioDisplay™ and third-party human-machine interfaces (HMIs), to databases, and to other information technology (IT) systems.

The controller communicates over standard TCP/IP Ethernet networks at 10 or 100 Mbps. It can be attached to existing wired or wireless Ethernet networks or be used in an independent control network built with standard, off-the-shelf Ethernet hardware. Communication with a SNAP-LCE controller can also be established via a modem connection using Point-to-Point Protocol (PPP), with firmware version 5.1c and newer. Wireless or wireline modem connections are ideal for remote locations where an Ethernet network is not practical.

The SNAP-LCE controller includes a 10/100 Mbps Fast Ethernet port for networking through an Ethernet switch to SNAP Simple, SNAP



SNAP-LCE

Ethernet, and SNAP Ultimate I/O units, which provide the connections to digital and analog sensors and actuators as well as serial devices. (Please note that SNAP Simple, Ethernet, and Ultimate I/O units have been replaced by SNAP PAC I/O units.)

The controller also includes two serial ports for use with a modem connection using PPP or for general-purpose communication with serial devices (requires firmware version 5.1c or newer). Using this option, you can send and receive data from one or two serial devices connected directly to the controller, rather than requiring a SNAP serial communication module on an attached I/O unit. Your ioControl strategy controls communication with the devices and uses the data as needed in control logic. Note that these two ports are not isolated from each other.

The SNAP-LCE simultaneously runs up to 16 ioControl flowcharts, plus the host task. The control strategy can contain a much larger number of flowcharts, however; the total number is limited only by the 8 MB of controller memory available for strategy storage.

Since the SNAP-LCE and the I/O units it controls have IP addresses like other devices on an Ethernet network, the number of points the controller can address is theoretically unlimited. The SNAP-LCE can control many SNAP Ethernet-based I/O units. Because the controller scans I/O only when your strategy logic requests it, the exact number of I/O points it can scan—and the scanning performance—depend on the architecture of your strategy.

Part Numbers

Part	Description
SNAP-LCE	Small-footprint Ethernet-based industrial controller
SNAP-PSDIN	SNAP Controller DIN-Rail Adapter

Software

The SNAP-LCE controller is compatible with Opto 22's ioProject Basic software suite, which consists of three components:

- **ioControl Basic**—a graphical, flowchart-based programming tool for machine control and process applications. Using ioControl, you create, download, and run control programs on the SNAP-LCE controller. In addition to flowchart programming (with subroutine capability), ioControl includes a powerful, built-in scripting language based on C and other procedural languages.
- **ioDisplay Basic**—an intuitive HMI package for building operator interfaces for your Microsoft® Windows®-based clients communicating with a SNAP-LCE controller. ioDisplay offers a

full-featured HMI including alarming, trending, and a built-in library of 3,000 industrial automation graphics.

- **ioManager™**—a utility application used to assign an IP address to the SNAP-LCE, read or change basic controller configuration, and more. In addition, you can use ioManager to configure the I/O units that communicate with the controller and to read from or write to I/O units.

ioProject Basic is included on the CD that comes with the SNAP-LCE controller and is also available for download from our website at www.opto22.com. For communication using OLE for Process Control (OPC), you can purchase OptoOPCServer™, Opto 22's OPC 2.0-compliant server, separately.


Specifications:

Processor	32-bit ColdFire® 5407
Memory Total RAM Battery-backed RAM Flash EEPROM	16 MB 512 KB 8 MB (7 MB with firmware version 7.2)
Backup battery	3-volt CR2032 Lithium, user replaceable. Typical service life with power off: 5 years.
Host communication	Ethernet (10/100 Mbps) or PPP (dial-up and radio modem)
I/O communication	Ethernet (10/100 Mbps)
I/O unit compatibility	Opto 22 SNAP Simple I/O, SNAP Ethernet I/O, and SNAP Ultimate I/O units
Serial ports	Two RS-232 ports. Baud rate is soft-selectable from 150–115,200 kBd.
Power requirements	5.0–5.2 VDC at 1.2 A
Operating temperature	0 °C to 60 °C
Storage temperature	-40 °C to 85 °C
Humidity	0% to 95% relative humidity, non-condensing
Software	ioProject software suite (ioControl, ioDisplay, ioManager) Purchase OptoOPCServer separately to communicate using OPC.
Other features	FTP server/client with file system Real-time clock

SNAP-LCE Controller

Dimensions

Panel Mounting and Dimensions



SNAP-LCE Controller

Dimensions (continued)

DIN-Rail Mounting and Dimensions

Requires a SNAP-PSDIN adapter (purchased separately).

