

AC / DC FANS & ACCESSORIES


DC Fan 50x50x10mm (2"x .39") DC Fan



Motor
Brushless DC

Frame / Impeller
UL94V-0 Thermoplastic

Life Expectancy
Ball Bearing
60,000 hours
Sleeve
30,000 hours (L10)



Safety Approvals
UL, cUL, TUV

Power Connection
2x lead wires 300mm

Bearings
Dual Ball or
Sleeve

Operating Temp.: Ball -4F ~ 158F (-20C ~ +70C) Sleeve 14F ~ 122F (-10C ~ 50C)

Model Number	Speed (RPM)	Max. CFM	Noise (dB)	Volts	Voltage Range	Amps	Max. Static Pressure Inches
OD5010-05HB	5300	14	28	5	4~7	.36	.13
OD5010-05MB	4700	10	22			.28	.11
OD5010-12HB	5300	14	28	12	8~17	.30	.13
OD5010-12HS							
OD5010-12MB	4700	10	22			.24	.11
OD5010-12MS							
OD5010-24HB	5300	14	28	24	22~26	.28	.13
OD5010-24HS							
OD5010-24MB	4700	10	22			.26	.11
OD5010-24MS							
Ball Bearing ["B" suffix] Sleeve Bearing ["S" suffix]							