



**Controls low-level input signals.
Controls load voltage
60V to 600V.**

**GU PhotoMOS
(AQV210, AQV214H)**



mm inch



FEATURES

- 1. Controls low-level analog signals**
PhotoMOS relays feature extremely low closed-circuit offset voltage to enable control of low-level analog signals without distortion.
- 2. Control with low-level input signals**
- 3. Controls various types of loads such as relays, motors, lamps and solenoids.**
- 4. Optical coupling for extremely high isolation**
Unlike mechanical relays, the PhotoMOS relay combines LED and optoelectronic device to transfer signals using light for extremely high isolation.
- 5. Eliminates the need for a counter electromotive force protection diode in the drive circuits on the input side**

- 6. Stable on resistance**
- 7. Low-level off state leakage current**
- 8. Eliminates the need for a power supply to drive the power MOSFET**
A power supply used to drive the power MOSFET is unnecessary because of the built-in optoelectronic device. This results in easy circuit design and small PC board area.
- 9. Low thermal electromotive force (Approx. 1 μV)**

RoHS Directive compatibility information
<http://www.mew.co.jp/ac/e/environment/>

TYPICAL APPLICATIONS

- High-speed inspection machines
- Telephone equipment
- Data communication equipment
- Computer

TYPES

Type	I/O isolation	Output rating*		Part No.				Packing quantity	
		Load voltage	Load current	Through hole terminal	Surface-mount terminal		Tube	Tape and reel	
					Tube packing style				Tape and reel packing style
AC/DC	Standard 1,500 V AC	60V	550 mA	AQV212	AQV212A	AQV212AX	AQV212AZ	1 tube contains 50 pcs. 1 batch contains 500 pcs.	1,000 pcs.
		100 V	320 mA	AQV215	AQV215A	AQV215AX	AQV215AZ		
		200 V	180 mA	AQV217	AQV217A	AQV217AX	AQV217AZ		
		350 V	130 mA	AQV210	AQV210A	AQV210AX	AQV210AZ		
		400 V	120 mA	AQV214	AQV214A	AQV214AX	AQV214AZ		
		600 V	50 mA	AQV216	AQV216A	AQV216AX	AQV216AZ		
	Reinforced 5,000 V	400 V	120 mA	AQV214H	AQV214HA	AQV214HAX	AQV214HAZ		

*Indicate the peak AC and DC values.

Note: For space reasons, the SMD terminal shape indicator "A" and the package style indicator "X" or "Z" are not marked on the relay.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item	Sym- bol	Type of connec- tion	AQV212(A)	AQV215(A)	AQV217(A)	AQV210(A)	AQV214(A)	AQV216(A)	AQV214H(A)	Remarks	
			Input	LED forward current	I _F	50 mA					
	LED reverse voltage	V _R	5 V								
	Peak forward current	I _{FP}	1 A							f = 100 Hz, Duty factor = 0.1%	
	Power dissipation	P _{in}	75 mW								
Output	Load voltage (peak AC)	V _L	60 V	100 V	200 V	350 V	400 V	600 V	400 V		
	Continuous load current	I _L	A	0.55 A	0.32 A	0.18 A	0.13 A	0.12 A	0.05 A	0.12 A	A connection: Peak AC, DC; B, C connection: DC
			B	0.65 A	0.42 A	0.22 A	0.15 A	0.13 A	0.06 A	0.13 A	
			C	0.80 A	0.60 A	0.30 A	0.17 A	0.15 A	0.08 A	0.15 A	
	Peak load current	I _{peak}	1.2 A	0.96 A	0.54 A	0.4 A	0.3 A	0.15 A	0.3 A	A connection: 100 ms (1 shot), V _L =DC	
	Power dissipation	P _{out}	500 mW								
	Total power dissipation	P _T	550 mW								
	I/O isolation voltage	V _{iso}	1,500 V AC						5,000 V AC		
Temperature limits	Operating	T _{opr}	-40°C to +85°C -40°F to +185°F							Non-condensing at low temp.	
	Storage	T _{stg}	-40°C to +100°C -40°F to +212°F								

GU PhotoMOS (AQV210, AQV214H)


2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item		Sym- bol	Type of connec- tion**	AQV212(A)	AQV215(A)	AQV217(A)	AQV210(A)	AQV214(A)	AQV216(A)	AQV214H(A)	Condition	
Input	LED operate current	Typical	—	1 mA	1 mA	1 mA	1 mA	1 mA	1 mA	1.3 mA	I _L = Max.	
		Maximum		3 mA	3 mA	3 mA	3 mA	3 mA	3 mA	3 mA		
	LED turn off current	Minimum	—	0.4 mA	0.4 mA	0.4 mA	0.4 mA	0.4 mA	0.4 mA	0.4 mA	1.2 mA	I _L = Max.
Typical		0.79 mA		0.79 mA	0.79 mA	0.79 mA	0.79 mA	0.79 mA	0.79 mA			
LED dropout voltage	Typical	V _F	—	1.25 V (1.14 V at I _F = 5 mA)							I _F = 50 mA	
	Maximum			1.5 V								
Output	On resistance	Typical	R _{on}	A	0.83 Ω	2.3 Ω	11.0 Ω	23 Ω	30 Ω	70 Ω	30 Ω	I _F = 5 mA I _L = Max. Within 1 s on time
		Maximum			2.5 Ω	4.0 Ω	15.0 Ω	35 Ω	50 Ω	120 Ω	50 Ω	
		Typical	R _{on}	B	0.44 Ω	1.15 Ω	5.5 Ω	11.5 Ω	22.5 Ω	55 Ω	22.5 Ω	I _F = 5 mA I _L = Max. Within 1 s on time
		Maximum			1.25 Ω	2.0 Ω	7.5 Ω	17.5 Ω	25 Ω	100 Ω	25 Ω	
		Typical	R _{on}	C	0.25 Ω	0.6 Ω	2.8 Ω	6.0 Ω	11.3 Ω	28 Ω	11.3 Ω	I _F = 5 mA I _L = Max. Within 1 s on time
		Maximum			0.63 Ω	1.0 Ω	3.8 Ω	8.8 Ω	12.5 Ω	50 Ω	12.5 Ω	
Output capacitance	Typical	C _{out}	A	150 pF	110 pF	70 pF	45 pF	45 pF	45 pF	45 pF	I _F = 0 mA V _B = 0 V f = 1 MHz	
Off state leakage current	Maximum	—	—	1 μA							I _F = 0 mA V _L = Max.	
Transfer characteristics	Switching speed	Turn on time*	T _{on}	—	0.65 ms	0.6 ms	0.25 ms	0.25 ms	0.21 ms	0.28 ms	0.6 ms	I _F = 5 mA** I _L = Max.
					Maximum	2 ms	2 ms	1.0 ms	0.5 ms	0.5 ms	0.5 ms	
		Turn off time*	T _{off}	—	0.08 ms	0.06 ms	0.05 ms	0.05 ms	0.05 ms	0.04 ms	0.05 ms	I _F = 5 mA I _L = Max.
					Maximum	0.2 ms	0.2 ms	0.2 ms	0.2 ms	0.2 ms	0.2 ms	
I/O capacitance	Typical	C _{iso}	—	0.8 pF							f = 1 MHz V _B = 0 V	
	Maximum			1.5 pF								
Initial I/O isolation resistance	Minimum	R _{iso}	—	1,000 MΩ							500 V DC	

Note: Recommendable LED forward current
Standard type: I_F = 5 mA
Reinforced type: I_F = 5 mA

For type of connection.

*Turn on/Turn off time




- For Dimensions.
- For Schematic and Wiring Diagrams.
- For Cautions for Use.

REFERENCE DATA

1-(1). Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F


Type of connection: A



1-(2). Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F

Type of connection: A



2-(1). On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;
LED current: 5 mA; Load voltage: Max. (DC)
Continuous load current: Max. (DC)

