




Panasonic
ideas for life

Greatly increase load current
(2.5A).
Load voltage is 60V.

HE PhotoMOS
(AQV252G)



mm inch



FEATURES

1. Greatly increased load current in the same package size.
2. Greatly improved specs allow you to use this in place of mercury and mechanical relays.

TYPICAL APPLICATIONS

- Crime and fire prevention market (use in I/O for alarm and security devices, etc.)
- Measuring instrument market (circuit testers, etc.)

TYPES

Type	Output rating*		Part No.				Packing quantity	
			Through hole terminal	Surface-mount terminal				
	Load voltage	Load current	Tube packing style		Tape and reel packing style		Tube	Tape and reel
Picked from the 1/2/3-pin side					Picked from the 4/5/6-pin side			
AC/DC type	60 V	2.5 A	AQV252G	AQV252GA	AQV252GAX	AQV252GAZ	1 tube contains 50 pcs. 1 batch contains 500 pcs.	1,000 pcs.

*Indicate the peak AC and DC values.

Note: For space reasons, the SMD terminal shape indicator "A" and the package type indicator "X" and "Z" are omitted from the seal.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	Type of connection	AQV252G(A)	Remarks	
Input	LED forward current	I_F		50 mA		
	LED reverse voltage	V_R		5 V		
	Peak forward current	I_{FP}		1 A	$f = 100 \text{ Hz}$, Duty factor = 0.1%	
	Power dissipation	P_{in}		75 mW		
Output	Load voltage (peak AC)	V_L		60 V		
	Continuous load current (peak AC)	I_L		A	2.5 A	A connection: Peak AC, DC B, C connection: DC
				B	3.5 A	
				C	5.0 A	
	Peak load current	I_{peak}		6.0 A	100ms (1 shot), $V_L = \text{DC}$	
Power dissipation	P_{out}	500 mW				
Total power dissipation		P_T		550 mW		
I/O isolation voltage		V_{iso}		1,500 V AC		
Temperature limits	Operating	T_{opr}		-40°C to +85°C -40°F to +185°F	Non-condensing at low temperatures	
	Storage	T_{stg}		-40°C to +100°C -40°F to +212°F		


HE PhotoMOS (AQV252G)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item			Symbol	Type of connection	AQV252G(A)	Condition
Input	LED operate current	Typical	I_{Fon}	—	0.5 mA	$I_L = 100\text{mA}$
		Maximum			3 mA	
	LED turn off current	Minimum	I_{Foff}	—	0.2 mA	$I_L = 100\text{mA}$
		Typical			0.45 mA	
	LED dropout voltage	Typical	V_F	—	1.32 V (1.14 V at $I_F = 5\text{ mA}$)	$I_F = 50\text{ mA}$
		Maximum			1.5 V	
Output	On resistance	Typical	R_{on}	A	0.08 Ω	$I_F = 5\text{ mA}$ $I_L = \text{Max.}$ Within 1 s on time
		Maximum			0.12 Ω	
		Typical	R_{on}	B	0.04 Ω	
		Maximum			0.06 Ω	
		Typical	R_{on}	C	0.02 Ω	
		Maximum			0.03 Ω	
	Off state leakage current	Maximum	I_{Leak}	—	1 μA	
Transfer characteristics	Turn on time*	Typical	T_{on}	—	1.1 ms	$I_F = 5\text{ mA}$ $I_L = 100\text{ mA}$ $V_L = 10\text{ V}$
		Maximum			5.0 ms	
	Turn off time*	Typical	T_{off}	—	0.25 ms	$I_F = 5\text{ mA}$ $I_L = 100\text{ mA}$ $V_L = 10\text{ V}$
		Maximum			0.5 ms	
	I/O capacitance	Typical	C_{iso}	—	0.8 pF	$f = 1\text{ MHz}$ $V_B = 0\text{ V}$
		Maximum			1.5 pF	
Initial I/O isolation resistance	Minimum	R_{iso}	—	1,000 M Ω	500 V DC	

Note: Recommendable LED forward current $I_F = 5$ to 10 mA.


*Turn on/Turn off time



REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to $+85^\circ\text{C}$
 -40°F to $+185^\circ\text{F}$



2. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;
LED current: 5 mA; Load voltage: Max. (DC)
Continuous load current: Max.(DC)



3. Turn on time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: 10 V (DC);
Continuous load current: 100 mA (DC)

