



Lower output capacitance and on resistance. (C×R20)
High speed switching. (Turn on time: 0.04ms, Turn off time: 0.06ms).

RF PhotoMOS (AQY221N1S)



mm inch



FEATURES

1. Low output capacitance between output terminals and low ON-resistance

Output capacitance(C): 2.0pF (typ.)
ON resistance(R): 9.8Ω (typ.)

2. High speed switching

Turn on time: 40ms
Turn off time: 60ms

3. SO package 4-pin type in super miniature design

Size: (W)4.3 × (L)4.4 × (H)2.1 mm
(W).169 × (L).173 × (H).083 inch

4. Low-level off state leakage current

The SSR has an off state leakage current of several milliamperes, where as this PhotoMOS relay has typ. 10pA (typical) even with the rated load voltage

5. Controls low-level analog signals

6. Low thermal electromotive force (Approx. 1 mV)

TYPICAL APPLICATIONS

Measuring and testing equipment

1. Testing equipment for semiconductor performance
IC tester, Liquid crystal driver tester, semiconductor performance tester
2. Board tester
Bear board tester, In-circuit tester, function tester
3. Medical equipment
Ultrasonic wave diagnostic machine
4. Multi-point recorder (warping, thermo couple)

TYPES

Type	Output rating*		Package size	Part No.			Packing quantity	
	Load voltage	Load current		Tube packing style	Tape and reel packing style		Tube	Tape and reel
AC/DC type	40V	120mA	SOP4pin	AQY221N1S	AQY221N1SX (Picked from the 1/2-pin side)	AQY221N1SZ (Picked from the 3/4-pin side)	1 tube contains: 100 pcs. 1 batch contains: 2,000 pcs.	1,000 pcs.

* Indicate the peak AC and DC values.

Note: For space reasons, the initial letters of the part number "AQY", the SMD terminal shape indicator "S" and the packaging style indicator "X" or "Z" are not marked on the relay.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	AQY221N1S	Remarks
Input	LED forward current	I _F	50mA	
	LED reverse voltage	V _R	5V	
	Peak forward current	I _{FP}	1A	f=100 Hz, Duty factor=0.1%
	Power dissipation	P _{in}	75mW	
Output	Load voltage (peak AC)	V _L	40V	
	Continuous load current	I _L	0.12A	Peak AC,DC
	Peak load current	I _{peak}	0.30A	100 ms (1 shot), V _L = DC
	Power dissipation	P _{out}	300mW	
Total power dissipation		P _T	350mW	
I/O isolation voltage		V _{iso}	1,500V AC	
Temperature limits	Operating	T _{opr}	-40°C to +85°C -40°F to +185°F	Non-condensing at low temperatures
	Storage	T _{stg}	-40°C to +100°C -40°F to +212°F	

RF PhotoMOS (AQY221N1S)


2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item		Symbol	AQY221N1S	Condition		
Input	LED operate current	Typical	0.9mA	$I_L=100\text{ mA}$		
		Maximum	3.0mA			
	LED turn off current	Minimum	0.4mA	$I_L=100\text{ mA}$		
		Typical	0.85mA			
LED dropout voltage	Typical	1.25V (1.14V at $I_F=5\text{mA}$)		$I_F=50\text{mA}$		
	Maximum	1.5V				
Output	On resistance #	Typical	9.8Ω	$I_F=5\text{mA}$ $I_L=100\text{ mA}$ Within 1 s on time		
		Maximum	12.5Ω			
	Output capacitance #	Typical	2.2pF	$I_F=0\text{mA}$ $V_B=0\text{V}$ $f=1\text{ MHz}$		
		Maximum	2.5pF			
Off state leakage current	Typical	0.01nA	$I_F=0\text{mA}$ $V_L=\text{Max.}$			
	Maximum	10nA				
Transfer characteristics	Switching speed	Turn on time*	Typical	0.04ms	$I_F=5\text{mA}$ $V_L=10\text{V}$ $R_L=100\Omega$	
			Maximum	0.5ms		
		Turn off time*	Typical	0.06ms		$I_F=5\text{mA}$ $V_L=10\text{V}$ $R_L=100\Omega$
			Maximum	0.2ms		
	I/O capacitance	Typical	0.8pF	$f=1\text{MHz}$ $V_B=0\text{V}$		
		Maximum	1.5pF			
Initial I/O isolation resistance	Minimum	R_{iso}	1,000MΩ	500V DC		

Note: Recommendable LED forward current $I_F = 5\text{mA}$.

For type of connection.

*Turn on/Turn off time




Other types of products than the C_{out} (typ. 2.0pF) and R_{on} (A connection typ. 9.8 ohm) combinations carried in this catalog are also available. (There is a trade-off between R_{on} and C_{out} both cannot be reduced at the same time.) For more information, please contact our sales office in your area.

- For Dimensions.
- For Schematic and Wiring Diagrams.
- For Cautions for Use.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to $+85^{\circ}\text{C}$
 -40°F to $+185^{\circ}\text{F}$



2. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 3 and 4
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)



3. Turn on time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)

