World Leader in Network and Electrical Solutions

Printer Friendly

HOME | SOLUTIONS | RESOURCES | PRODUCTS | SERVICES | LEARNING

SEARCH

Current refinements (click x to remove)

Search Tips 👩

ict i annily a Disconnect Adapter, Non-insulated M rext dearth. D-2

Your search criteria matched only one product, shown below.



- \bullet Couples two female disconnects to one male disconnect (all .250 x .032)
- Multiple connection points allow additional circuits to be added to existing equipment without expensive rework
- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost

Related Products

Male Disconnect, Non-Insulated - Bu... Female Disconnect, Non-Insulated &#.. Wire and Cable Stripping Tools

Part Number:	D-250A-C
RoHS Compliancy Status:	Compliant
Part Description:	Disconnect Adapter, 22-18 AWG wire, couples two female and one male tab (all .250 \times .032), non-insulated.
Product Type:	Disconnects
Length (In.):	.82
Width (In.):	.57
Angle:	extra angle
Tab Size (In.):	.250 x .032
Min. Order UOM:	PC
Min. Order Qty.:	100
BOM Qty. (# of Pkgs.)	

Add to My Catalog

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

View Content Details

Evaluate Design a Solution Install & Maintain

Part Drawings:

Disconnect Adapter, Non-Insulated: D-2...

Design a Solution

Part Drawings:

Disconnect Adapter, Non-Insulated: D-250A pdf

legal information | privacy policy | site map

┢


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

.32

(8.1)

NOTES:

- 1. D-250A DISCONNECT ADAPTER
 COUPLES TWO FEMALE DISCONNECTS
 TO ONE MALE DISCONNECT
 ALL .250 X .032 (6.3 X 0.8)
- 2. MATERIAL:
 A. STAMPING: TIN PLATED BRASS
- 3. PACKAGE QTY:
 A. STD: -C = 100
 B. BULK: -M = 1000
- 4. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS
- 5. MAXIMUM OPERATING TEMPERATURE: 130 C°



— .37 —

(9.4)

.25 ±.005 (6.3)

 $.25 \pm .005$

(6.3)

 $.57 \pm .01$

(14.5)

06	9/04	JHNU	J	ADDED NOTE 5.				A41323_06	
05	1/01	RM	SKB	FILESPEC WAS N41323AA_PCD_04	08925	JAC	ССН		
04	12/94	ΤH		ADDED TOLERANCES	02707			CORP. TINLEY PARK, ILLINOIS	
03	5/92	ВК	RLS	UPDATED NOTES TAB WIDTH DIMENSION WAS .25 (6.4)	00967		KS	.250 (6.3) DISCONNECT ADAPTER D-250A	
2	8-88	DW		REDRAWN WITH REVISIONS			JB	230 (0.3) DISCONNECT ADAPTER D-230A	
REV	DATE	BY	CHK	DESCRIPTION	ECN #	CUST	РМ	DAW CHK'D CJH SCALE NONE PRAWING NO. A41323	