
PANDUIT *

F1.5X3WH6-A



Choose from 29 sizes of PANDUIT® Type F Wiring Duct from 0.5" x 0.5" up to 4.0" x 5.0". Used
for general purpose control panel wiring in communication closets. Ideal for use with high-density
terminal blocks. The non-slip cover conceals all wiring and is easy to install. The duct and cover
form a flush sidewall providing increased capacity and improved aesthetics.

Specifications

- Made of lead-free PVC
- UL Recognized continuous use temperature: 122°F (50°C)
- UL94 Flammability Rating of V-0
- Conforms with NFPA 79-2002 section 14.3.1 requirement for flame retardant material
- Available in Light Gray and White
- Provided with mounting holes

Features and Benefits

- Narrow finger/slot design allows further fanning of wires for neater wire management in highdensity control panels
- PANDUIT® exclusive rounded edges protects hands and wiring/cabling from abrasion
- Non-slip cover stays in place during shipment, vibration and when in a vertical orientation, eliminating rework
- Flush cover design holds 10-12% more wires than traditional duct designs
- Double scoreline allows quick modification for larger cabling bundles saving installation time leading to a lower installed cost
- Specially formulated lead-free material eliminates health concerns associated with PVC that contains lead
- Double restricted slot design retains wire in slot for fast, easy wire installation or removal
- Base and cover sold separately.

■ Part Number	F1.5X3WH6-A
■ RoHS Compliancy Status	Compliant
■ Part Description	Narrow finger, slotted wiring duct
■ Material	PVC
■ Color	White
■ CSA Certified	Yes
 Adhesive Mounting Tape 	Yes
■ CE Compliant	Yes
■ Duct Size W x H (In.)	1.75 x 3.12
Duct Size W x H (mm)	44.5 x 79.2
■ Mounting Method	Standard Mounting Holes with Adhesive
■ Pricing Description	Slotted Duct, PVC,1.5"X3"X6' Adh., White
■ Slot Width (In.)	0.2
■ Slot Width (mm)	5

■ Min. Order UOM FT	
■ Min. Order Qty. 6	

■ BOM Qty. (# of Pkgs.)