PANDUIT *

F3X4WH6



Choose from 29 sizes of PANDUIT® Type F Wiring Duct from 0.5" x 0.5" up to 4.0" x 5.0". Used
for general purpose control panel wiring in communication closets. Ideal for use with high-density
terminal blocks. The non-slip cover conceals all wiring and is easy to install. The duct and cover
form a flush sidewall providing increased capacity and improved aesthetics.

Specifications

- Made of lead-free PVC
- UL Recognized continuous use temperature: 122°F (50°C)
- UL94 Flammability Rating of V-0
- Conforms with NFPA 79-2002 section 14.3.1 requirement for flame retardant material
- Available in Light Gray and White
- Provided with mounting holes

. Features and Benefits

- Narrow finger/slot design allows further fanning of wires for neater wire management in highdensity control panels
- PANDUIT® exclusive rounded edges protects hands and wiring/cabling from abrasion
- Non-slip cover stays in place during shipment, vibration and when in a vertical orientation, eliminating rework
- Flush cover design holds 10-12% more wires than traditional duct designs
- Double scoreline allows quick modification for larger cabling bundles saving installation time leading to a lower installed cost
- Specially formulated lead-free material eliminates health concerns associated with PVC that contains lead
- Double restricted slot design retains wire in slot for fast, easy wire installation or removal
- Base and cover sold separately.

Part Number	F3X4WH6
■ RoHS Compliancy Status	Compliant
Part Description	Narrow finger, slotted wiring duct.
■ Material	Lead-Free PVC
Color	White
CSA Certified	Yes
Length (ft.)	6
CE Marking	Yes
☐ Duct Size W x H (In.)	3.25 x 4.10
■ Duct Size W x H (mm)	82.6 x 104.1
Mounting Method	Standard Mounting Holes
Pricing Description	Slotted Duct,PVC,3"X4"X6',White
Slot Width (In.)	0.20
Slot Width (mm)	5.0

Cover Part Number	C3WH6
Min. Order UOM	FT
Min. Order Qty.	6
■ BOM Qty. (# of Pkgs.)	